


RoHS

齒輪形狀：B



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	


標準軸孔



TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑	DH	L				
(S45C) HCWGT HCWGTT HCWGTH	2.0	B	15	20	10~15	30	34	24	35				
			16		10~16	32	36	26					
			18		10~21	36	40	30					
			19			38	42	32					
			20		10~23	40	44	34					
			22		10~25	44	48	38					
			24		10~28	48	52	42					
			25			50	54						
			26		10~29	52	56	45					
			28		10~31	56	60	50					
			30		10~33	60	64	52					
			(SUS304) HCWGP				32	12~35		64	68	56	80
							34			68	72	60	
							35	12~36		70	74	62	
36	12~38	72		76			64						
40	12~42	80		84			70						
42		84		88			72						
45		90		94			74						
48	12~43	96		100			76						
50		100		104			78						

追加工

Alteration	Code	Spec.
	AT	鍵槽孔
	BT	圓孔+攻牙
	CT	鍵槽孔+攻牙
止付螺絲孔追加工	BT90	止付螺絲孔90°
	CT90	增加1孔
止付螺絲孔追加工	BT120	止付螺絲孔120°
	CT120	增加1孔



對照表

d H7	M
4~8	M3
9~12	M4
13~17	M5
18~30	M6
31~45	M8
46~60	M10

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 追加工詳細請參閱P.503

訂貨：TYPE - M - Y - T - B - d - (追加工) Code

HCWGT - 2.0 - B - 24 - 20 - 10

HCWGTH - 2.0 - B - 42 - 20 - 12 - AT

HCWGT - 2.0 - B - 50 - 20 - 16 - BT90

交期：8天 S45C

12天 SUS304