



RoHS



扳手





本體		銷子			彈簧				
材質	處理	材質	處理	顏色	輕荷重	中荷重	重荷重	輕荷重	重荷重
鋼	鍍鉍	鋼	表面硬化、鍍鉍	白	SUS	鋼	鋼	鋼	鍍鉍
		POM	-			鋼	鋼	鋼	鍍鉍

品號	備註	A	B	C -2	D	F	P(N)≈ max.	WS	質量 (g)	庫存
22150.0310	鋼銷 無膠封 輕荷重	M12	5	11.5	6.4	1.6	20	10	4.0	•
22150.0314				19.0					5.9	•
22150.0318				26.5					7.9	•
22150.0330			6	11.5	10.4	2.0	40		4.8	•
22150.0334				19.0					6.6	•
22150.0338		M18×1.5	10	26.5	16.9	3.2	100	16	8.6	•
22150.0350				18.0					19.0	•
22150.0354				31.5					28.0	•
22150.0358				45.0					36.0	•
22150.0311	鋼銷 無膠封 中荷重	M12	5	11.5	6.4	1.6	50	10	4.1	•
22150.0315				19.0					6.4	•
22150.0319				26.5					8.3	•
22150.0331			6	11.5	10.4	2.0	75		4.9	•
22150.0335				19.0					7.1	•
22150.0339		M18×1.5	10	26.5	16.9	3.2	150	16	9.6	•
22150.0351				18.0					20.0	•
22150.0355				31.5					29.0	•
22150.0359				45.0					39.0	•
22150.0312	鋼銷 無膠封 重荷重	M12	5	11.5	6.4	1.6	100	10	4.4	•
22150.0316				19.0					6.9	•
22150.0320				26.5					9.0	•
22150.0332			6	11.5	10.4	2.0	40		5.4	•
22150.0336				19.0					7.7	•
22150.0340		M18×1.5	10	26.5	16.9	3.2	200	16	10.0	•
22150.0352				18.0					21.0	•
22150.0356				31.5					30.0	•
22150.0360				45.0					40.0	•
22150.0370	塑膠銷 無膠封 輕荷重	M12	5	11.5	6.4	1.6	20	10	2.7	•
22150.0373			6	11.5	10.4	2.0	40		3.1	•
22150.0375			5	19.0	6.4	1.6	20		4.6	•
22150.0380			6	19.0	10.4	2.0	40		4.8	•
22150.0383			5	26.5	6.4	1.6	20		6.5	•
22150.0385		6	26.5	10.4	2.0	40	6.8	•		
22150.0390		M18×1.5	10	18.0	16.9	3.2	100	16	12.0	•
22150.0393				31.5					20.0	•
22150.0395				45.0					30.0	•
22150.0820	M12			-					-	-
22150.0822	M18×1.5	-	-	-	-	-	-	137.0	•	

Wa. 注意

- ・鋼銷使用溫度max.250℃
塑膠銷使用溫度max.80℃
- ・P(N)是銷子移動的最大力量
- ・裝置方法請參考後頁

Ex. 使用例


 訂貨： 交期： 天

22150.0310