


RoHS

齒輪形狀：A



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	

標準軸孔



圓孔

TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑			
(S45C) HCWGT HCWGTT HCWGTH	2.5	A	15	24	10~20	37.5	42.5			
			16		10~22	40	45			
			18		10~26	45	50			
			19		10~27	47.5	52.5			
			20		10~28	50	55			
			22		10~30	55	60			
			24		10~33	60	65			
			25		10~35	62.5	67.5			
			26		12~38	65	70			
			28		12~42	70	75			
			30		12~45	75	80			
			(SUS304) HCWGP				32	12~49	80	85
							34		85	90
35	87.5	92.5								
36	12~52	90		95						
40	12~56	100		105						
42	15~56	105		110						
45		112.5		117.5						
48	15~59	120		125						
50		125	130							

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 軸孔追加加工詳細請參閱P.503

軸孔追加加工

Alteration	Code	Spec.
	AT	鍵槽孔

訂貨： TYPE - M - Y - T - B - d - (錫加工 Code)

HCWGT - 2.5 - A - 28 - 24 - 16

HCWGTH - 2.5 - A - 50 - 24 - 15 - AT

交期： 8 天 S45C

12 天 SUS304