


(RoHS)

齒輪形狀：B



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	


標準軸孔



TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑	DH	L				
(S45C) HCWGT HCWGTT HCWGTH	2.5	B	15	24	10~20	37.5	42.5	30	40				
			16		10~22	40	45	32					
			18		10~26	45	50	38					
			19		10~27	47.5	52.5	40					
			20		10~28	50	55	42					
			22		10~30	55	60	46					
			24		10~33	60	65	50					
			25		10~35	62.5	67.5	55					
			26		12~38	65	70						
			28		12~42	70	75	60					
			30		12~45	75	80	65					
			(SUS304) HCWGP				32			12~49	80	85	70
							34				85	90	75
							35			87.5	92.5	78	
36	12~52	90		95			80						
40	12~56	100		105									
42	15~56	105		110									
45		112.5		117.5									
48	15~59	120		125			90						
50		125		130									

追加工

	Alteration	Code	Spec.
軸孔追加工		AT	鍵槽孔
		BT	圓孔+攻牙
		CT	鍵槽孔+攻牙
止付螺絲孔追加工		BT90	止付螺絲孔90°
		CT90	增加1孔
		BT120	止付螺絲孔120°
		CT120	增加1孔



對照表

d H7	M
4~8	M3
9~12	M4
13~17	M5
18~30	M6
31~45	M8
46~60	M10

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 追加工詳細請參閱P.503

訂貨： TYPE - M - Y - T - B - d - (追加工 Code)

HCWGT - 2.5 - B - 24 - 24 - 16

HCWGTH - 2.5 - B - 42 - 24 - 15 - AT

HCWGTH - 2.5 - B - 50 - 24 - 16 - BT90

交期： 8 天 S45C

12 天 SUS304