


RoHS

齒輪形狀：A



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	

標準軸孔



圓孔

TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑
(S45C) HCWGT HCWGTT HCWGTH	3.0	A	15	28	12~24	45	51
			16		12~28	48	54
			18		12~30	54	60
			19		12~31	57	63
			20		12~35	60	66
			22		12~37	66	72
			24		12~40	72	78
			25		12~42	75	81
			26		12~45	78	84
			28		12~49	84	90
			30		12~52	90	96
			32			96	102
(SUS304) HCWGP			34	15~56	102	108	
			35		105	111	
			36		108	114	
			40	15~59	120	126	
			42		126	132	
			45		135	141	
			48		144	150	
			50		150	156	

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 軸孔追加加工詳細請參閱P.503

軸孔追加加工

Alteration	Code	Spec.
	AT	鍵槽孔

訂貨： TYPE - M - Y - T - B - d - (錫加工 Code)

HCWGT - 3.0 - A - 30 - 28 - 16

HCWGTH - 3.0 - A - 48 - 28 - 30 - AT

交期： 8 天 S45C

12 天 SUS304