


(RoHS)

齒輪形狀：B



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	

標準軸孔




圓孔

TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑	DH	L				
(S45C) HCWGT HCWTT HCWGTH	3.0	B	15	28	12~24	45	51	36	46				
			16		12~28	48	54	38					
			18		12~30	54	60	42					
			19		12~31	57	63	48					
			20		12~35	60	66	50					
			22		12~37	66	72	55					
			24		12~40	72	78	60					
			25		12~42	75	81	65					
			26		12~45	78	84	65					
			28		12~49	84	90	70					
			30		12~52	90	96	75					
			32			96	102	85					
			(SUS304) HCWGP				34	15~56		102	108	90	100
							35			105	111		
36	108	114											
40	15~59	120		126			100						
42		126		132									
45		135		141									
48		144		150									
50	150	156											

追加工

Alteration	Code	Spec.
	AT	鍵槽孔
	BT	圓孔+攻牙
	CT	鍵槽孔+攻牙
止付螺絲孔追加工	BT90 CT90	止付螺絲孔90° 增加1孔
	BT120 CT120	止付螺絲孔120° 增加1孔



對照表

d H7	M
4~8	M3
9~12	M4
13~17	M5
18~30	M6
31~45	M8
46~60	M10

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 追加工詳細請參閱P.503

訂貨：TYPE - M - Y - T - B - d - (追加工 Code)

HCWGT - 3.0 - B - 24 - 28 - 16

HCWGTH - 3.0 - B - 30 - 28 - 12 - AT

HCWGTH - 3.0 - B - 48 - 28 - 16 - BT90

交期：8 天 S45C

12 天 SUS304