



RoHS




TYPE	材質	處理
PS40SD	S45C	齒面淬火
PS50SD		

TYPE	T 齒數	d <sub>H8</sub> 指定單位1		D	Dp	輪骨		B	C	重量 Kg ≈	備註
		最小	最大			DH	L				
PS40SD	12	11	17	55	49.07	34	35	7.2	27.8	0.33	40B
	13		20	59	53.07	38				0.40	
	14		24	63	57.07	42				0.49	
	15		25	67	61.08	46				0.57	
	16	14	28	71	65.10	50				0.66	
	17		32	76	69.12	54				0.76	
	18		35	80	73.14	59				0.89	
	19		37	84	77.16	63				1.00	
	20	15	40	88	81.18	67				1.14	
	21		43	92	85.21	71				1.23	
PS50SD	12	15	24	69	61.34	43	40	8.7	31.3	0.63	50B
	13		25	74	66.34	48				0.75	
	14		30	79	71.34	53				0.90	
	15		35	84	76.35	58				1.04	
	16		37	89	81.37	63				1.22	
	17		42	94	86.39	68				1.41	
	18		44	100	91.42	73				1.61	
	19		46	105	96.45	79				1.80	
	20		50	110	101.48	84				1.95	
	21		54	115	106.51	89				2.27	

追加工

	Alteration	Code	Spec.
軸孔追加工		AT	鍵槽孔
		BT	圓孔+攻牙
		CT	鍵槽孔+攻牙
止付螺絲孔追加工		BT90	止付螺絲孔
		CT90	90°增加1孔
		BT120	止付螺絲孔
		CT120	120°增加1孔



對照表

d <sub>H7</sub>	M
4~8	M3
9~12	M4
13~17	M5
18~30	M6
31~45	M8
46~60	M10

PS 備註

- 非規格品歡迎洽詢
- 追加工詳細請參閱P.503
- 接受圖面詢價，可依圖面生產

訂貨： TYPE - T - d - (追加工 Code) 交期： 18 天

PS40SD - 20 - 15

PS50SD - 20 - 25 - AT