


RoHS



Type		材質			處理
中心軸承	兩端軸承	本體	法蘭	軸承	
WWBK	WWBKA	鋁合金	鋁合金	鋼	白陽極
TWBK	TWBKA	≈S45C	SPCC		染黑
NWBK	NWBKA				無電解鍍


中心軸承型 (1PCS軸承時)

WWBK  
TWBK  
NWBK




中心軸承型 (2PCS軸承時)

WWBK  
TWBK  
NWBK



兩端軸承型

WWBKA  
TWBKA  
NWBKA



Type	型式		軸徑 d	P.D.	O.D.	F	E	A	W	S	軸承		
	齒數	配合皮帶									No.(參考)	D	B
WWBK TWBK NWBK	16	L050	10	48.51	47.75	55	40	14	19	5	6200ZZ×1	30	9
		L075						21	26	8.5			
		L100						14	19	4.5			
	18	L050	12	54.57	53.81	61	45	21	26	8	6201ZZ×1	32	10
		L075						27	32	6			
		L100						14	19	4.5			
	20	L050	12	60.64	59.88	67	50	21	26	8	6201ZZ×1	32	10
		L075						27	32	6			
		L100						14	19	4.5			
	22	L050	15	66.70	65.94	80	60	14	19	4	6202ZZ×1	35	11

Type	型式		軸徑 d	P.D.	O.D.	F	E	A	W	Dh	軸承		
	齒數	配合皮帶									No.(參考)	D	B
WWBKA TWBKA NWBKA	14	L050	8	42.45	41.68	48	35	14	19	16.5	698ZZ×2	19	6
		L075						21	26				
		L100						27	32				
		L150						40	45				
	15	L050	8	45.48	44.72	48	35	14	19	16.5	698ZZ×2	19	6
		L075						21	26				
		L100						27	32				
		L150						40	45				
	16	L050	8	48.51	47.75	55	40	14	19	16.5	698ZZ×2	19	6
		L075						21	26				
		L100						27	32				
		L150						40	45				
	16	L050	10	48.51	47.75	55	40	14	19	19.5	6900ZZ×2	22	6
		L075						21	26				
		L100						27	32				
		L150						40	45				
	18	L050	12	54.57	53.81	61	45	14	19	25	6001ZZ×2	28	8
		L075						21	26				
		L100						27	32				
		L150						40	45				
	20	L075	15	60.64	59.88	67	50	21	26	29	6002ZZ×2	32	9
		L100						27	32				
		L150						40	45				
	22	L075	15	66.70	65.94	80	60	21	26	29	6002ZZ×2	32	9
L100		27						32					
L150		40						45					
30	L050	12	90.96	90.20	99	80	14	19	22	6901ZZ×2	24	6	
	L075						21	26					
	L100						27	32					
	L150						40	45					

兩端軸承型

訂貨：

Type - 齒數 - 配合皮帶 - d 交期: 15 天  
 TWBKA - 20 - L100 - 15