



|      |        |
|------|--------|
| 本體   | 螺栓     |
| 材質   | 材質     |
| S45C | SCM435 |

(PBB軸環)標準E型

| Type | 軸孔徑<br>d | 使用螺栓 |       | 拆卸<br>攻牙孔 | 最大容許<br>扭矩<br>N.m | 容許<br>推力荷重<br>KN | 螺栓<br>緊固扭矩<br>N.m | D    | D <sub>1</sub> | D <sub>2</sub> | d <sub>1</sub> | L    | ℓ |    |      |
|------|----------|------|-------|-----------|-------------------|------------------|-------------------|------|----------------|----------------|----------------|------|---|----|------|
|      |          | 數量   | 尺寸    |           |                   |                  |                   |      |                |                |                |      |   |    |      |
| PBB  | 8        | 4    | M3x12 | M3x2      | 16                | 4.00             | 2.0               | +0.1 | 19             | 10.0           | 3.3            | 15.5 | 4 |    |      |
|      | 10       |      |       |           | 39                |                  |                   |      |                |                |                |      |   | 22 | 12.0 |
|      | 11       |      |       |           | 43                |                  |                   |      |                |                |                |      |   |    |      |
|      | 12       | 48   | 24    | 14.0      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 14       | 73   |       |           | 27                | 16.6             |                   |      |                |                |                |      |   |    |      |
|      | 15       | 78   | 28    | 17.6      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 16       | 83   |       |           | 29                | 18.6             |                   |      |                |                |                |      |   |    |      |
|      | 17       | 88   | 30    | 19.6      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 18       | 154  |       |           | 33                | 20.6             |                   |      |                |                |                |      |   |    |      |
|      | 19       | 163  | 35    | 22.4      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 20       | 171  |       |           | 36                | 23.4             |                   |      |                |                |                |      |   |    |      |
|      | 22       | 186  | 38    | 24.6      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 24       | 206  |       |           | 40                | 26.6             |                   |      |                |                |                |      |   |    |      |
|      | 25       | 216  | 42    | 28.4      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 28       | 353  |       |           | 44                | 30.6             |                   |      |                |                |                |      |   |    |      |
|      | 30       | 382  | 47    | 33.4      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 32       | 412  |       |           | 49                | 34.7             |                   |      |                |                |                |      |   |    |      |
|      | 35       | 451  | 53    | 38.4      |                   |                  |                   |      |                |                |                |      |   |    |      |
|      | 38       | 686  |       |           | 58                | 42.0             |                   |      |                |                |                |      |   |    |      |
|      | 40       | 725  | 59    | 43.5      |                   |                  |                   |      |                |                |                |      |   |    |      |
| 42   | 757      | 62   |       |           | 46.0              |                  |                   |      |                |                |                |      |   |    |      |
| 45   | 1490     |      | 69    | 49.5      |                   |                  |                   |      |                |                |                |      |   |    |      |
| 48   | 1600     | 72   |       |           | 52.5              |                  |                   |      |                |                |                |      |   |    |      |
| 50   | 1660     |      | 74    | 54.5      |                   |                  |                   |      |                |                |                |      |   |    |      |

(PGG軸環)短型F型

| Type | 軸孔徑<br>d | 使用螺栓  |       | 拆卸<br>攻牙孔 | 最大容許<br>扭矩<br>N.m | 容許<br>推力荷重<br>KN | 螺栓<br>緊固扭矩<br>N.m | D    | D <sub>1</sub> | D <sub>2</sub> | d <sub>1</sub> | L    | ℓ |    |       |
|------|----------|-------|-------|-----------|-------------------|------------------|-------------------|------|----------------|----------------|----------------|------|---|----|-------|
|      |          | 數量    | 尺寸    |           |                   |                  |                   |      |                |                |                |      |   |    |       |
| PGG  | 6        | 3     | M3x10 | M3x3      | 5.6               | 1.87             | 1.9               | +0.1 | 16             | 8.5            | 3.3            | 10.5 | 3 |    |       |
|      | 8        |       |       |           | 8.5               |                  |                   |      |                |                |                |      |   | 21 | 12.75 |
|      | 10       |       |       |           | 18.0              |                  |                   |      |                |                |                |      |   |    |       |
|      | 11       | 20.0  | 23    | 14.75     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 12       | 23.0  |       |           | 26                | 17.65            |                   |      |                |                |                |      |   |    |       |
|      | 14       | 37.0  | 27    | 18.65     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 15       | 39.0  |       |           | 28                | 19.65            |                   |      |                |                |                |      |   |    |       |
|      | 16       | 42.0  | 29    | 20.65     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 17       | 45.0  |       |           | 30                | 21.85            |                   |      |                |                |                |      |   |    |       |
|      | 18       | 48.0  | 32    | 22.85     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 19       | 49.0  |       |           | 36                | 24.1             |                   |      |                |                |                |      |   |    |       |
|      | 20       | 97.0  | 37    | 25.75     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 22       | 110.0 |       |           | 39                | 27.75            |                   |      |                |                |                |      |   |    |       |
|      | 24       | 121.0 | 41    | 28.75     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 25       | 124.0 |       |           | 43                | 31.75            |                   |      |                |                |                |      |   |    |       |
|      | 28       | 141.0 | 46    | 33.75     |                   |                  |                   |      |                |                |                |      |   |    |       |
|      | 30       | 149.0 |       |           | 47                | 35.75            |                   |      |                |                |                |      |   |    |       |
|      | 32       | 163.0 | 50    | 39.1      |                   |                  |                   |      |                |                |                |      |   |    |       |
| 35   | 173.0    |       |       |           |                   |                  |                   |      |                |                |                |      |   |    |       |

PS. 備註

- 請以軸的公差為g6、軸的表面粗糙度Ra6.3為基準
- PGG軸環無開縫
- 使用溫度:-20~+80°C

訂貨： Type - d 交期： 10 天  
PBB - 12