




RoHS



Type	型式			材質			處理		
	皮帶寬度	皮帶寬度	皮帶寬度	皮帶輪	法蘭	軸環	皮帶輪	法蘭	軸環
	10.0mm	15.0mm	25.0mm						
	A:11 W:16	A:17 W:22	A:27 W:32						
	S5M100	S5M150	S5M250						
GBDW	○	○	○	鋁合金	鋁合金	≈S45C	白陽極		
GBDF	○	○	○				硬質陽極		
GBDM	○	○	○				無電解鍍		
GBSD	○	○	○	≈S45C	SPCC		染黑		
GBDH	○	○	○				無電解鍍		

軸孔徑選擇

dH7	最大容許扭矩 N·m		D		(L)
	PBB軸環	PGG軸環	PBB軸環	PGG軸環	
8	16	8.5	25.5	24.5	8.5
10	39	18	30.0	29.0	
11	43	20	31.0	30.0	10.5
12	48	23	32.0	31.0	
14	73	37	35.0	36.0	12.0
15	78	39	36.0	37.0	
16	83	42	37.0	38.0	13.0
17	88	45	38.0	39.0	
18	154	48	43.0	40.0	
19	163	49	45.0	42.0	
20	171	97	46.0	46.0	14.0
22	186	110	48.0	47.0	
24	206	121	50.0	49.0	
25	216	124	52.0	51.0	
28	353	141	54.0	53.0	15.5
30	382	149	57.0	56.0	
32	412	163	59.0	58.0	16.5
35	451	173	63.0	61.0	
38	686	-	70.0	-	19.0
40	725	-	71.0	-	
42	757	-	74.0	-	20.0



齒數

mm	22	24	25	26	28	30	32	34	36	40	44	48	50	60	72
P.D.	35.01	38.20	39.79	41.38	44.56	47.75	50.93	54.11	57.30	63.66	70.03	76.39	79.58	95.49	114.59
O.D.	34.05	37.24	38.83	40.42	43.60	46.79	49.97	53.15	56.34	62.70	69.07	75.43	78.62	94.53	113.63
F	40	45	45	48	48	52	55	61	61	67	74	83	87	99	119
E	27	30	30	35	35	36	40	45	45	50	58	63	67	80	100

型式			dH7範圍(～)指定單位1mm							
Type	齒數	種類 皮帶寬度 No.	皮帶輪 形狀	E型			F型			
				S5M100 PBB軸環	S5M150 PBB軸環	S5M250 PBB軸環	S5M100 PGG軸環	S5M150 PGG軸環	S5M250 PGG軸環	
GBDW GBDF GBDM GBSD GBDH	22	S5M100 A:11 W:16	E F	8	-		-			
	24			8·10	10	8				
	25			8·10·12	10·12	8	8·10·12			
	26	10·12·14·15			10·12					
	28	10·12·14·17			10·12		10·12·14·17			
	30	S5M150 A:17 W:22		12·14·20·22·24·25			-			
	32			12·14·20·22·24·25·28			12			
	34			12·14·20·22·24·25·28·30·32		12·14·20·22·24·25·28·30·32				
	36			24·25·28·30		12·14·20·22·24·25·28·30·32·35·38·40				
	40			32		12·14·20·22·24·25·28·30·32·35·38·40·42				
	44			S5M250 A:27 W:32	12·14·20·22·24·25·28·30·32			12·14·20·22·24·25·28·30·32		
	48				12·14·20·22·24·25·28·30·32			12·14·20·22·24·25·28·30·32		
	50	24·25·28·30			12·14·20·22·24·25					
	60	32			28·30·32·35					
72										

PS. 備註

· 適用於MITSUBOSHI BELTING(株)以及BANDO(株)的S5M型

訂貨： 型式 - 皮帶輪形狀 - 軸孔徑 交期： 15 天

GBDW30S5M150 - E - 10