






Type	型式				材質			處理		
	皮帶寬度 15.0mm	皮帶寬度 25.0mm	皮帶寬度 30.0mm	皮帶寬度 40.0mm	皮帶輪	法蘭	軸環	皮帶輪	法蘭	軸環
	A:17 W:22 S8M150	A:28 W:33 S8M250	A:33 W:38 S8M300	A:44 W:49 S8M400						
GBDW	○	○	○	○	鋁合金	鋁合金	≈S45C	白陽極		-
GBDF	○	○	○	○				硬質陽極		
GBSD	○	○	○	○	≈S45C	SPCC		染黑		
GBDH	○	○	○	○				無電鍍		

軸孔徑選擇

dH7	最大容許扭矩N·m		D		(L)
	PBB軸環	PGG軸環	PBB軸環	PGG軸環	
12	48	23	32	31	10.5
14	73		35		12.0
15	78		36		
16	83		37		13.0
17	88		38		
18	154		43		
19	163		45		
20	171		46		14.0
22	186		48		
24	206		50		
25	216		52		
28	353		54		15.5
30	382		57		
32	412	163	59	58	16.5
35	451	173	63	61	
38	686		70		19.0
40	725		71		
42	757		74		20.0
45	1490		84		
48	1600		87		24.5
50	1660		89		



齒數

mm	18	19	20	21	22	24	25	26	28	30	32	34	36	38	40	44	48	50	60	72
P.D.	45.84	48.38	50.93	53.48	56.02	61.12	63.66	66.21	71.30	76.39	81.49	86.58	91.67	96.77	101.86	112.05	122.23	127.32	152.79	183.35
O.D.	44.46	47.01	49.56	52.10	54.65	59.74	62.29	64.84	69.93	75.02	80.12	85.21	90.30	95.39	100.49	110.67	120.86	125.95	151.42	181.97
F	52	55	58	61	61	67	70	74	80	87	95	99	104	111	119	127	135	160	190	
E	36	40	40	45	45	50	56	58	60	67	67	75	80	84	90	100	105	115	140	170

型式		dH7範圍(～)指定單位1mm											
Type	齒數	種類 皮帶寬度 No.	皮帶輪 形狀	E型				F型					
				S8M150 PBB軸環	S8M250 PBB軸環	S8M300 PBB軸環	S8M400 PBB軸環	S8M150 PGG軸環	S8M250 PBB軸環:12~30 PGG軸環:32·35	S8M300 PBB軸環:15~32 PGG軸環:35	S8M400 PBB軸環		
GBDW GBDF GBSD GBDH	18	S8M150 A:17 W:22	E	12			-	-	12				
	19			12·14·15	15		-		12·14·15	15			
	20												
	21												
	22		S8M250 A:28 W:33	E	12·14~17	15~17	16·17		12	12·14~17	15~17	16·17	
	24												
	25												
	26												
	28		S8M300 A:33 W:38	F	14~20·22·24	15~20·22·24	16~20·22·24			14~20·22·24	15~20·22·24	16~20·22·24	
	30												
	32												
	34												
	36		S8M400 A:44 W:49	F	16~20·22·24·25·28·30·32·35					16~20·22·24		16~20·22·24·25·28·30·32·35	
	38												
40													
44													
48				20·22·24·25·28·30·32·35·38·40·42							20·22·24·25·28·30		
50				20·22·24·25·28·30·32							32·35·38·40·42		
60				35·38·40·42·45·48·50									
72				20·22·24·25·28·30·32·35·38·40·42·45·48·50								20·22·24·25·28·30·32·35·38·40·42·45·48·50	

PS. 備註

· 適用於MITSUBOSHI BELTING(株)以及BANDO(株)的S8M型

訂貨： 型式 - 皮帶輪形狀 - 軸孔徑 交期： 15 天

GBDF40S8M250 - E - 30