




RoHS



Type	型式		材質			處理		
	皮帶寬度 10.0mm	皮帶寬度 15.0mm	皮帶輪	法蘭	軸環	皮帶輪	法蘭	軸環
	A:11.6 W:16 P5M100	A:16.6 W:21 P5M150						
SBDW	○	○	鋁合金	鋁合金	≈S45C	白陽極		
SBDM	○	○				無電解鍍		-
SBDN	○	○	≈S45C	SPCC	≈S45C	染黑		
SBDH	○	○				無電解鍍		

軸孔徑選擇

dH7	最大容許扭矩N·m		D		(L)
	PBB軸環	PGG軸環	PBB軸環	PGG軸環	
8	16	8.5	25.5	24.5	8.5
10	39	18	30.0	29.0	
11	43	20	31.0	30.0	10.5
12	48	23	32.0	31.0	
14	73		35.0		
15	78		36.0		12.0
16	83		37.0		
17	88		38.0		13.0
18	154		43.0		
19	163		45.0		
20	171		46.0		14.0
22	186		48.0		
24	206		50.0		
25	216		52.0		
28	353		54.0		15.5
30	382		57.0		
32	412		59.0		
35	451		63.0		16.5
38	686		70.0		
40	725		71.0		19.0
42	757		74.0		



齒數

mm	22	24	25	26	28	30	32	34	36	40	44	48	50	60	72
P.D.	35.01	38.20	39.79	41.38	44.56	47.75	50.93	54.11	57.30	63.66	70.03	76.39	79.58	95.49	114.59
O.D.	33.87	37.06	38.65	40.24	43.42	46.60	49.79	52.97	56.15	62.52	68.89	75.25	78.44	94.35	113.45
F	40	44	44	48	50	55	55	61	67	67	74	83	87	104	119
E	28	32	32	36	38	40	40	46	50	50	58	63	67	84	100

型式			dH7範圍(~)指定單位1mm						
Type	齒數	種類 皮帶寬度 No.	皮帶輪 形狀	E型		F型			
				P5M100 PBB軸環	P5M150 PBB軸環	P5M100 PGG軸環	P5M150 PGG軸環		
SBDW SBDM	22	P5M100 A:11.6 W:16	E	8					
	24			8·10·11					
	25			8					
	26			8·10·12·14					
	28			8·10·12·14·16		8·10~12			
	30			10~12·14~17					
	32			10~12					
	34			10~12·14~20·22					
	36			P5M150 A:16.6 W:21	F	10~12·14~20·22·24·25			
	40					12·14~20·22·24·25·28			
44	12·14~20·22·24·25·28·30·32·35								
48	12·14~20·22·24·25								
50	12·14~20·22·24·25		12·14~20·22·24·25						
60	28·30·32·35·38								
72	28·30·32·35·38·40·42								

型式			dH7範圍(~)指定單位1mm		
Type	齒數	種類 皮帶寬度 No.	皮帶輪 形狀	E型	
				P5M100 PBB軸環	P5M150 PBB軸環
SBDN SBDH	22	P5M100 A:11.6 W:16	E	8	
	24			10·12	
	26			12	
	28			12·14·15	
	30			-	
	32			-	
	36			P5M150 A:16.6 W:21	15~24
44	-				
50	-				
60	-				

PS. 備註

· 適用於MITSUBOSHI BELTING(株)以及BANDO(株)的P5M型

訂貨： 型式 - 皮帶輪形狀 - 軸孔徑 交期： 15 天

SBDW30P5M100 - E - 10