









本體		優力膠
材質	處理	材質
SS400	染黑	WAT-SBU
SUS304	-	15

型式1

型式2



型式1				線軌尺寸	對應廠商產品			W	H	A	B	P	T	M
鐵		不銹鋼			IKO	NSK	THK							
品號	庫存	品號	庫存											
WAT-LSWU-01	△	WAT-LSWU-01S	△	15	-	-	SRS15M	32	15.0	7.5	13	16	19	M5×10
WAT-LSWU-04	△	WAT-LSWU-04S	△	20	-	-	SRS20M		17.5	10.0	18			
WAT-LSWU-05	△	WAT-LSWU-05S	△	25			SRS25M		22.5	15.0				

型式2				線軌尺寸	對應廠商產品			W	H	A	B	E	F	P	T	M
鐵		不銹鋼			IKO	NSK	THK									
品號	庫存	品號	庫存													
WAT-LSWU-02	△	WAT-LSWU-02S	△	15	LWH15	LS15AL	HSR15A	32	22	14.5	18	12	8	16	25	M5
WAT-LSWU-03	△	WAT-LSWU-03S	△		-	LH15AN	-		26	18.5						
WAT-LSWU-06	△	WAT-LSWU-06S	△	20	LWH20	LS20AL·LH20AN	HSR20A		31	23.5	23		12	18	32	
WAT-LSWU-07	△	WAT-LSWU-07S	△	25	LWH25	LH25AL	HSR25A	34	26.5							
WAT-LSWU-08	△	WAT-LSWU-08S	△	30	LWH30	LS30AL·LH30AL	HSR30A	38	40	32.5	28	16	16	20	38	M8
WAT-LSWU-09	△	WAT-LSWU-09S	△	35	LWH35	LS35AL·LH35AL	HSR35A	45	46	38.5	31					

Ps. 備註

- 使用在線軌的防脫落和位置定位
- 附優力膠型可消除衝擊音量

Wa. 注意

- 以上產品是本公司自訂規格；記載之對應廠商產品，請貴客戶自行確認

訂貨： 交期： 天

WAT-LSWU-01