









本體		型式1		型式2		固定銷
材質	處理	材質	處理	材質	處理	
SS400	染黑	S45C	染黑	SCM435	染黑	SUJ2
SUS304	-	S45C	鉻酸鹽 (白色)	SUSXM7	-	

型式1

型式2



型式1				線軌 尺寸	對應廠商產品			W	H	A	B	P	P <sub>1</sub> ±0.02	e	T	M (細牙)	D	d H7	附屬品		
鐵		不銹鋼			IKO	NSK	THK												螺絲		固定銷
品號	庫存	品號	庫存																		
WAT-LSY-01N	△	WAT-LSY-01SN	△	15	-	SRS15M	32	15	8.5	13	16	16	4	19	M6×P0.75	5.5	4×6	M5×20	4×10		
WAT-LSY-04N	△	WAT-LSY-04SN	△	20	-	SRS20M	19	10.0	18	18	18	6	25	M8×P1.0	6.6	M6×25					
WAT-LSY-05N	△	WAT-LSY-05SN	△	25	-	SRS25M	23	15.0	18	18	18	6	25	M8×P1.0	6.6	M6×25					

型式2				線軌 尺寸	對應廠商產品			W	H	A	B	E	F	P	P <sub>1</sub> ±0.02	e	T	M (細牙)	D	d H7	附屬品		
鐵		不銹鋼			IKO	NSK	THK														螺絲		固定銷
品號	庫存	品號	庫存																				
WAT-LSY-02N	△	WAT-LSY-02SN	△	15	LWH15	LS15AL	HSR15A	22	15.5	-	-	-	8	16	16	25	M6×P0.75	5.5	4×6	M5×12	4×10		
WAT-LSY-03N	△	WAT-LSY-03SN	△	20	-	LH15AN	-	26	19.5	18	12	12	16	16	6	32	M8×P1.0	6.6		M6×12			
WAT-LSY-06N	△	WAT-LSY-06SN	△	25	-	LS25AL	-	31	23.0	23	18	18	18	18	8	45	M8×P1.0	9.0		5×8		M8×16	5×12
WAT-LSY-07N	△	WAT-LSY-07SN	△	30	LWH20	LS20AL·LH20AN	HSR20A	32	26	18	12	12	16	16	6	32	M8×P1.0	9.0	5×8	M8×16	5×12		
WAT-LSY-08N	△	WAT-LSY-08SN	△	30	LWH30	LS30AL·LH30AL	HSR30A	38	40	32.0	28	16	16	20	20	8	45	M8×P1.0	9.0	5×8	M8×16	5×12	
WAT-LSY-09N	△	WAT-LSY-09SN	△	35	LWH35	LS35AL·LH35AL	HSR35A	45	46	38.0	31	16	16	20	20	8	45	M8×P1.0	9.0	5×8	M8×16	5×12	

**Ps.** 備註

· 使用在線軌的防脫落和位置定位

**Wa.** 注意

· 以上產品是本公司自訂規格；記載之對應廠商產品，請貴客戶自行確認

訂貨：  交期： 天

WAT-LSY-01N