



<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	h <sub>3</sub> min.
40	M 8	16	8,4	26	14	23,5
50	M 10	20	10,5	32	17	29
63	M 12	26	13	40	21	36

**Specification**

- Plastic Technopolymer (Polyamide PA)
  - Shock-resistant
  - Black, matte finish
- Bushing
  - Steel —
  - Zinc plated, blue passivated
  - Stainless steel AISI 303 **NI**
- *Plastic Characteristics* → Page 2158
- *Stainless Steel Characteristics* → Page 2166
- RoHS



**Information**

Quick release star knobs GN 6336.3 are used in such applications where the knob has to be completely removed after the releasing operation and refitted rapidly for re-clamping.

The knob is tilted over the threaded spindle. When in position, the knob is brought into a straight position for meshing of the two threads on nut and spindle. The knob will then have to be turned only by fraction of a rotation to achieve clamping.

Functional safety exists only if the clamping surface lies at a right angle to the threaded bolt.

see also...

- *Quick Release Knurled Nuts GN 6303.1* → Page 644
- *Quick Release Star Knobs GN 6336.3 with Loss Protection GN 111.7* → Page 2084

How to order (Bushing steel)	<sup>1</sup> d <sub>1</sub>
	<sup>2</sup> d <sub>2</sub>
<b>GN 6336.3-50-M10</b>	

How to order (Bushing stainless steel)	<sup>1</sup> d <sub>1</sub>
	<sup>2</sup> d <sub>2</sub>
	<sup>3</sup> Material (bushing)
<b>GN 6336.3-40-M8-NI</b>	