


RoHS



Type	材質
BOM	①②本體 優力膠

Type	型 式		齒 數	皮帶周長 (mm)
	皮帶No.	皮帶寬度No.		
BOM (優力膠)	60XL	025 (6.4mm)	60	152.40
	70XL		70	177.80
	80XL		80	203.20
	90XL		90	228.60
	96XL		96	243.84
	100XL		100	254.00
	110XL		110	279.40
	114XL		114	289.56
	120XL		120	304.80
	130XL		130	330.20
	140XL		140	355.60
	150XL		150	381.00
	154XL		154	391.16
	156XL		156	396.24
	160XL		160	406.40
	166XL	166	421.64	
	168XL	168	426.72	
	170XL	170	431.80	
	176XL	176	447.04	
	180XL	180	457.20	
	190XL	031 (7.9mm)	190	482.60
	198XL		198	502.92
	200XL		200	508.00
	202XL	202	513.08	
	210XL	037 (9.5mm)	210	533.40
	212XL		212	538.48
	220XL		220	558.80
	230XL		230	584.20
	236XL		236	599.44
	240XL		240	609.60
	250XL		250	635.00
	254XL		254	645.16
	260XL		260	660.40
	290XL		050 (12.7mm)	290
	300XL	300		762.00
	320XL	320		812.80
	330XL	330		838.20
	376XL	376		955.04
	396XL	396		1005.84
	414XL	414		1051.56
	430XL	430		1092.20
	460XL	460		1168.40
478XL	478	1214.12		
480XL	480	1219.20		
490XL	490	1244.60		
512XL	512	1300.48		
564XL	564	1432.56		
630XL	630	1600.20		
670XL	670	1701.80		
730XL	730	1854.20		

## 【Wa.】注意

- ・使用溫度：-橡膠：30～90℃，優力膠：0～80℃（參考值）
- ・產品示意圖顏色僅供參考，材質會因時間而產生變化
- ・皮帶顏色僅供參考，詢價、訂購時請告知顏色

訂貨： Type - 皮帶 No. - 皮帶寬度 No. 交期： 3 天  
BOM - 120XL - 050