



RoHS



Type	材質	
BTM	①背面橡膠	CR合成橡膠
	②齒紋橡膠	
	③齒布	尼龍帆布

Type	型式		齒數	皮帶周長 (mm)
	皮帶No.	皮帶寬度No.		
BTM (橡膠)	185H	075 (19.1mm)	37	469.9
	210H		42	533.4
	220H		44	558.8
	225H		45	571.5
	230H		46	584.2
	240H		48	609.6
	245H		49	622.3
	255H		51	647.7
	270H		54	685.8
	280H		56	711.2
	285H		57	723.9
	300H		60	762.0
	305H	61	774.7	
	310H	62	787.4	
	315H	63	800.1	
	320H	64	812.8	
	330H	66	838.2	
	340H	68	863.6	
	350H	70	889.0	
	360H	72	914.4	
	370H	74	939.8	
	375H	75	952.5	
	380H	76	965.2	
	390H	78	990.6	
	400H	80	1016.0	
	410H	82	1041.4	
	420H	84	1066.8	
	430H	86	1092.2	
	440H	88	1117.6	
	450H	90	1143.0	
	465H	93	1181.1	
	480H	96	1219.2	
	490H	98	1244.6	
	500H	100	1270.0	
	510H	102	1295.4	
	520H	104	1320.8	
	530H	106	1346.2	
	540H	108	1371.6	
	560H	112	1422.4	
	565H	113	1435.1	
	570H	114	1447.8	
	580H	116	1473.2	
590H	118	1498.6		
600H	120	1524.0		
605H	121	1536.7		
615H	123	1562.1		
620H	124	1574.8		

Type	型式		齒數	皮帶周長 (mm)
	皮帶No.	皮帶寬度No.		
BTM (橡膠)	625H	075 (19.1mm)	125	1587.5
	630H		126	1600.2
	640H		128	1625.6
	650H		130	1651.0
	660H		132	1676.4
	680H		136	1727.2
	700H		140	1778.0
	725H		145	1841.5
	730H		146	1854.2
	740H		148	1879.6
	750H		150	1905.0
	760H		152	1930.4
	770H	154	1955.8	
	780H	156	1981.2	
	800H	160	2032.0	
	810H	162	2057.4	
	820H	164	2082.8	
	840H	168	2133.6	
	850H	170	2159.0	
	860H	172	2184.4	
	880H	176	2235.2	
	900H	180	2286.0	
	950H	190	2413.0	
	960H	192	2438.4	
	985H	197	2501.9	
	1000H	200	2540.0	
	1020H	204	2590.8	
	1050H	210	2667.0	
	1100H	220	2794.0	
	1120H	224	2844.8	
	1130H	226	2870.2	
	1135H	227	2882.9	
	1140H	228	2895.6	
	1150H	230	2921.0	
	1155H	231	2937.7	
	1180H	236	2997.2	
	1185H	237	3009.9	
	1200H	240	3048.0	
	1250H	250	3175.0	
	1325H	265	3365.5	
	1345H	269	3416.3	
	1350H	270	3429.0	
1400H	280	3556.0		
1460H	292	3708.4		
1510H	302	3835.4		
1680H	336	4267.2		
1700H	340	4318.0		

注意

- ・使用溫度:橡膠:-30~90℃,優力膠:0~80℃(參考值)
- ・皮帶顏色僅供參考,詢價、訂購時請告知顏色

訂貨: Type - 皮帶No. - 皮帶寬度No. 交期: 3 天
BTM - 185H - 075