



Type	材質	
GBTM	①背面橡膠	CR合成橡膠
	②齒紋橡膠	
	③齒布	

Type	型式		齒數	皮帶周長 (mm)
	皮帶No.	皮帶寬度No.		
GBTM (橡膠)	S5M255	100 (10mm)	51	255.0
	S5M275		55	275.0
	S5M295		59	295.0
	S5M300		60	300.0
	S5M320		64	320.0
	S5M325		65	325.0
	S5M350		70	350.0
	S5M375		75	375.0
	S5M390		78	390.0
	S5M400		80	400.0
	S5M410	82	410.0	
	S5M420	84	420.0	
	S5M425	85	425.0	
	S5M450	90	450.0	
	S5M475	95	475.0	
	S5M490	98	490.0	
	S5M500	100	500.0	
	S5M520	104	520.0	
	S5M550	110	550.0	
	S5M560	112	560.0	
	S5M565	113	565.0	
	S5M575	115	575.0	
	S5M600	120	600.0	
	S5M625	125	625.0	
	S5M635	127	635.0	
	S5M645	129	645.0	
	S5M650	130	650.0	
	S5M665	133	665.0	
	S5M670	134	670.0	
	S5M695	139	695.0	
	S5M700	140	700.0	
	S5M710	142	710.0	
	S5M725	145	725.0	

Type	型式		齒數	皮帶周長 (mm)
	皮帶No.	皮帶寬度No.		
GBTM (橡膠)	S5M740	100 (10mm)	148	740.0
	S5M750		150	750.0
	S5M770		154	770.0
	S5M775		155	775.0
	S5M800		160	800.0
	S5M810		162	810.0
	S5M830		166	830.0
	S5M850		170	850.0
	S5M860		172	860.0
	S5M870		174	870.0
	S5M900	180	900.0	
	S5M920	184	920.0	
	S5M940	188	940.0	
	S5M950	190	950.0	
	S5M965	193	965.0	
	S5M975	195	975.0	
	S5M1000	200	1000.0	
	S5M1025	205	1025.0	
	S5M1050	210	1050.0	
	S5M1125	225	1125.0	
	S5M1135	227	1135.0	
	S5M1145	229	1145.0	
	S5M1195	239	1195.0	
	S5M1225	245	1225.0	
	S5M1250	250	1250.0	
	S5M1270	254	1270.0	
	S5M1295	259	1295.0	
	S5M1350	270	1350.0	
	S5M1420	284	1420.0	
	S5M1595	319	1595.0	
	S5M1800	360	1800.0	
	S5M2000	400	2000.0	

Wa 注意

- ・使用溫度:橡膠:-30~90℃,優力膠:0~80℃(參考值)
- ・皮帶顏色僅供參考,詢價、訂購時請告知顏色

訂貨: Type - 皮帶No. - 皮帶寬度No. 交期: 3 天
GBTM - S5M255 - 100