



ROSTFREI
Inox
Stainless
Steel

d₁	d₂		d₃	e ≈	l₁	l₂	l₃	s
19	G 1/4	M 14 x 1,5	6	17,3	8	23	30,5	15
22	G 3/8	M 16 x 1,5	6	20,8	8	23	30,5	18
26	G 1/2	M 20 x 1,5	6	24,3	8,5	23,5	31	21
32	G 3/4	M 26 x 1,5	6	31,3	9	24	32	27
40	G 1	M 33 x 1,5	6	37	11	26	34,5	32

Specification

- Stainless steel AISI 316 LHC
Plain, tumbled
- Magnet
Alloy: AlNiCo
- Seal
Fluorine rubber (FPM / FKM)
- Brown
- Temperature resistant up to 180 °C
- *Magnet Characteristics* → Page QVX
- *Elastomer Characteristics* → Page QVX
- *Stainless Steel Characteristics* → Page QVX
- RoHS

On request

- Other thread sizes
- With acrylonitrile butadiene rubber (NBR) seal GN 738.4

Information

Stainless steel magnetic plugs GN 738.5 attract iron particles which might be floating in the fluid. The stainless steel makes them suitable for use in particularly aggressive environments.

To avoid breakage or demagnetization, the round magnets are fitted with a plastic distance and protection tube. This tube has to be removed prior to installing the plug.

The seal is embedded in a radial recess, and thus cannot be lost or squeezed out during tightening.

The outer diameter d_1 of stainless steel threaded plugs is matched to screw-in holes for pipe fittings according to DIN 3852.

see also...

- *Magnetic Plugs GN 738 / GN 738.1 (Aluminum)* → Page QVX
- *Stainless Steel Mounting Nuts GN 7430* → Page QVX
- *Stainless Steel Welding Sockets GN 7490* → Page QVX

How to order	1	d₁
	2	d₂

GN 738.5-22-M16X1,5

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9