



d₁=8



材質	處理
彈簧鋼	鍍鋅

品 號	華 司				max.軸向推力 (N)	適 用 軸					庫 存
	b	h	a	s		d ₁	d ₂	m	n	z	
10.08.0000.0004.014	8	10	2.5	0.3	700	4	3.2	0.64	2	0.5	•
10.08.0000.0005.014	9	11.2	2.5	0.4	900	5	4	0.74	2.5		•
10.08.0000.0006.014	11	13.2	3		1050	6	5		3		•
10.08.0000.0008.014	14	17.7	3.5	0.5	2500	8	6	0.94	3.5	0.75	•
10.08.0000.0010.014	18	22	3.8		4500	10	8	1.05	4.5		1
10.08.0000.0012.014	22	26.1	4.4		6700	12	9	1.15	5	•	
10.08.0000.0014.014	25.1	29.8	4.9	0.6	7900	14	10	1.25	5.5	1.25	•
10.08.0000.0016.014	28	34	6		9500	16	12	1.35	6	1.5	•

Ps. 備註

· 組立時不用工具亦可；組立工具，歡迎洽詢

Ex. 使用例

訂貨： 交期：

10.08.0000.0004.014

Sp. 特長

· 做為軸或銷和裝配件的晃動補償和固定

