



材質	處理
彈簧鋼	鍍鋅

品 號	華 司					max. 軸向推力 (N)	適 用 軸					單 價
	b	h <sub>1</sub>	h <sub>2</sub>	a	s		d <sub>1</sub> h11	d <sub>2</sub> h11	m +0.1	n	z	
10.09.0000.0003.014	4.4	4.8	3	1.9	0.4	730	3	2.3	0.64	1.5	0.5	•
10.09.0000.0004.014	6.6	7.2	4.3	2.8		1100	4	3.2		2		•
10.09.0000.0005.014	7.5	8.4	5.2			2.5	2100	5	4	0.74		•
10.09.0000.0006.014	10.6	11.3	6.8	3.5	0.5	3500	6	5	3		0.75	•
10.09.0000.0008.014	11.5	11.9	7.4	4.5		0.6	4000	8	6	0.94	3.5	1
10.09.0000.0010.014	15.5	16.3	9.5	5.9	6600		10	8	1.05	4.5	•	
10.09.0000.0012.014	16.8	18	10.5	6.2	7500		12	9	1.15	5	1.25	•
10.09.0000.0014.014	19.2	20	12.2	6.8	0.7	8900	14	10	1.25	5.5	1.5	•
10.09.0000.0016.014	22.7	24	14.3	7.6	0.8	9800	16-18	12	1.35	6		•
10.09.0000.0024.014	34	34	19	9.8	1	10500	20-25	16-18	1.8	8		•

**Ps.** 備註

· 組立時不用工具亦可；組立工具，歡迎洽詢

**Ex.** 使用例



訂貨：  交期：  天

10.09.0000.0003.014

**Sp.** 特長

· 做為軸或銷和裝配件的晃動補償和固定