

# MVS\*/MVD\* 系列

電磁閥



## 電磁閥 / 選用表

型號	閥類種類						本體型式		*A, B 配管口尺寸及有效斷面積 mm <sup>2</sup> (Cv 值)								閥體 寬度 (mm)	瓦特數 W (DC)	(*) 使用壓力範圍 MPa	型錄 頁次				
	3 口 2 位置		5 口 2 位置		5 口 3 位置		直配管型	連座型	M3	M5	1/8"	1/4"	3/8"	1/2"	3/4"	1"								
	常閉型	常開型	單動型	複動型	中間關閉	中間通氣																		
MVSC-220	●	●	●	●	●	●	●	●			18 (1.00)	18 (1.00)						22	2	0.2~0.8	1-5			
MVSC-260			●	●	●	●	●	●			18 (1.00)							26	2	0.2~0.8	1-10			
MVSC-300	●	●	●	●	●	●	●	●					35 (1.94)					30	2	0.2~0.8	1-13			
MVSC-460	●	●	●	●	●	●	●	●						50 (2.78)				30	2	0.2~0.8	1-17			
MVSC1-150			●						●		38 (0.21)							15	0.95	0.15~0.8	1-22			
MVSC1-180	●	●	●	●	●	●	●	●			12 (0.67)							18	0.95	0.15~0.8	1-24			
MVSC1-220	●	●	●	●	●	●	●	●			18 (1.00)	18 (1.00)						22	0.95	0.2~0.8	1-28			
MVSD1-180			●	●	●	●	●	●			12 (0.67)							18	2.9	0.15~0.8	1-33			
MVSE-260			●	●	●	●	●	●				18 (1.00)						26	2	0.2~1.2	1-37			
MVSE-300			●	●	●	●	●	●					35 (1.94)					30	2	0.2~1.2	1-40			
MVSE-500			●					●					41 (2.28)					30	2	0.2~1.2	1-43			
MVSE-510			●					●					65 (3.61)					68	10	0.2~0.7	1-45			
MVSE-600			●					●						115 (6.39)	135 (7.5)	68	10	0.2~0.7	1-47					
MVSF-100	●	●	●					●	●	1.0 (0.06)								10	0.55	0.15~0.7	1-49			
MVSI-260			●	●	●	●	●	●			22 (1.22)							35	2	0.2~0.7	1-53			
MVSI-450			●					●			27 (1.5)							45	2	0.2~0.7	1-55			
MVSI-510			●					●				65 (3.61)						68	10	0.2~0.7	1-60			
MVSN-220			●					●			18 (1.00)							22	2	0.2~0.7	1-62			
MVSN-300			●	●	●	●	●	●			35 (1.94)							30	2	0.2~0.8	1-64			
MVSP-156			●	●	●	●	●	●			11 (0.61)							15	0.95	0.15~0.7	1-67			
MVSP-188			●	●	●	●	●	●			15 (0.83)							18	0.95	0.15~0.7	1-72			
MVSY-100			●	●	●	●	●	●			4.5 (0.25)							10	0.55	0.2~0.8	1-76			
MVSY-156			●	●	●	●	●	●			11 (0.61)							15	0.55	0.15~0.7	1-80			
MVSY-188			●	●	●	●	●	●			15 (0.83)							18	0.55	0.15~0.7	1-86			
MVSZ-100			●					●			4.7 (0.26)							10	0.55	0.15~0.7	1-91			
MVDA-80	●							●			0.612 (0.034)							8	0.5	0~0.8	1-93			
MVDA-120	●							●			2.184 (0.121)							12	0.8	0~0.8	1-95			
MVDC-220	●							●			0.8 (0.044)							22	2	0.01~0.7	1-97			
MVDY-100	●							●			0.28 (0.016)							10	0.55	0~0.9	1-99			

● 2 口 2 位置及 3 口 2 位置常閉型。

\* 有效斷面積及使用壓力範圍為 5 口 2 位置之值。