



類型(底板)
4 C3


底座	螺桿	螺帽	橡膠墊	
材質	材質	材質	材質	硬度
SUS304	SUS303	SUS304	NBR	蕭氏A85±5




5
S型：無鎖緊螺帽
SK型：有鎖緊螺帽



5
V型：無鎖緊螺帽
VK型：有鎖緊螺帽



5
T型：無鎖緊螺帽
TK型：有鎖緊螺帽



5
W型：可調節套筒

TYPE	d ₁	d ₂	l ₁								l ₂				l ₃				庫存		
			S/SK				T/TK				V/VK				W						
GN17	60	M8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△	
	60	M10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	△	
	60	M12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	△	
	60	M16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	129	154	179	204	△
	80	M8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	80	M10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	80	M12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	80	M16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	131	156	181	206	△
	80	M20	-	-	-	-	75	100	125	150	200	250	100	125	150	200	155	180	205	255	△
	80	M24	-	-	-	-	100	125	150	200	300	-	100	150	200	-	179	229	279	-	△
	100	M8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	100	M10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	100	M12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	△
	100	M16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	133	158	183	208	△
	100	M20	-	-	-	-	75	100	125	150	200	250	100	125	150	200	157	182	207	257	△
	100	M24	-	-	-	-	100	125	150	200	300	-	100	150	200	-	181	231	281	-	△
120	M20	-	-	-	-	75	100	125	150	200	250	-	-	-	-	-	-	-	-	△	
120	M24	-	-	-	-	100	125	150	200	300	-	-	-	-	-	-	-	-	-	△	
120	M30	-	-	-	-	100	125	150	200	300	-	-	-	-	-	-	-	-	-	△	

訂貨： TYPE - ¹d₁ - ²d₂ - ³l_{1,2,3} - ⁴類型 - ⁵型式 交期： 10 天
GN17 - 100 - M12 - 60 - C3 - VK

TYPE	d ₁	d ₂			d ₃	h ₁	h ₂	h ₃	l ₄	l ₅	l ₆	S	A/F ₁	A/F ₂	A/F ₄	A/F ₅	A/F ₆	W°	
GN17	60	M8	M10	M12	-	31	-	-	-	-	-	2	17	-	-	-	-	32	
	60	M16	-	-	24	-	37	33	45	45	29	2	-	12	10	12	20	32	
	80	M8	M10	M12	-	33	-	-	-	-	-	2	17	-	-	-	-	26	
	80	M16	-	-	24	-	39	35	45	45	29	2	-	12	10	12	20	26	
	80	M20	-	-	30	-	39	36	56	56	36	2	-	15	13	16	24	26	
	80	M24	-	-	35	-	41	38	67	67	42	2	-	19	17	20	30	26	
	100	M8	M10	M12	-	35	-	-	-	-	-	2	17	-	-	-	-	22	
	100	M16	-	-	24	-	41	37	45	45	29	2	-	12	10	12	20	22	
	100	M20	-	-	30	-	41	38	56	56	36	2	-	15	13	16	24	22	
	100	M24	-	-	35	-	43	40	67	67	42	2	-	19	17	20	30	22	
	120	M20	-	-	-	-	43	-	-	-	-	2	-	15	-	-	-	-	20
	120	M24	-	-	-	-	46	-	-	-	-	2	-	19	-	-	-	-	20
	120	M30	-	-	-	-	50	-	-	-	-	2	-	24	-	-	-	-	20

SP. 特長

- 適用於侵蝕性環境
- 底板的傾斜表面有利於排水，有助於簡化清潔流程，並防止灰塵污垢的積聚
- 符合FDA標準的橡膠襯墊將底座密封可用於食品加工領域或製藥行業
- 螺帽規範：ISO 4032

PS. 備註

- 腳座出廠時已裝配好，不能拆卸

TYPE	d ₁	d ₂	靜荷重 kN			
			S/SK	T/TK	V/VK	W
GN17	60	M8	8	-	-	-
	60	M10	14	-	-	-
	60	M12	14	-	-	-
	60	M16	-	14	14	14
	80	M8	8	-	-	-
	80	M10	14	-	-	-
	80	M12	14	-	-	-
	80	M16	-	14	14	14
	80	M20	-	32	32	32
	80	M24	-	36	36	36
	100	M8	8	-	-	-
	100	M10	14	-	-	-
	100	M12	16	-	-	-
	100	M16	-	24	24	24
	100	M20	-	26	26	26
	100	M24	-	28	28	28
	120	M20	-	26	-	-
120	M24	-	26	-	-	
120	M30	-	26	-	-	