



類型(底板)  
4 C3

底座	螺桿	螺帽	橡膠墊	
材質	材質	材質	材質	硬度
SUS316L	SUS316L	SUS316	NBR	蕭氏A85±5



5  
S型：無鎖緊螺帽  
SK型：有鎖緊螺帽



5  
T型：無鎖緊螺帽  
TK型：有鎖緊螺帽

TYPE	d <sub>1</sub>	d <sub>2</sub>	l <sub>1</sub>									庫存	
			S/SK				T/TK						
GN18	60	M8	40	50	63	-	-	-	-	-	-	-	△
	60	M10	50	60	80	100	-	-	-	-	-	-	△
	60	M12	60	80	100	125	-	-	-	-	-	-	△
	60	M16	-	-	-	-	75	100	125	150	200	250	△
	80	M8	40	50	63	-	-	-	-	-	-	-	△
	80	M10	50	60	80	100	-	-	-	-	-	-	△
	80	M12	60	80	100	125	-	-	-	-	-	-	△
	80	M16	-	-	-	-	75	100	125	150	200	250	△
	80	M20	-	-	-	-	75	100	125	150	200	250	△
	80	M24	-	-	-	-	100	125	150	200	300	-	△
	100	M8	40	50	63	-	-	-	-	-	-	-	△
	100	M10	50	60	80	100	-	-	-	-	-	-	△
	100	M12	60	80	100	125	-	-	-	-	-	-	△
	100	M16	-	-	-	-	75	100	125	150	200	250	△
	100	M20	-	-	-	-	75	100	125	150	200	250	△
	100	M24	-	-	-	-	100	125	150	200	300	-	△
120	M20	-	-	-	-	75	100	125	150	200	250	△	
120	M24	-	-	-	-	100	125	150	200	300	-	△	

訂貨： TYPE - <sup>1</sup>d<sub>1</sub> - <sup>2</sup>d<sub>2</sub> - <sup>3</sup>l<sub>1</sub> - <sup>4</sup>類型 - <sup>5</sup>型式 交期： 10 天  
GN18 - 80 - M12 - 60 - C3 - SK

TYPE	d <sub>1</sub>	d <sub>2</sub>			h <sub>1</sub>	h <sub>2</sub>	S	A/F <sub>1</sub>	A/F <sub>2</sub>	W°
GN18	60	M8	M10	M12	31	-	2	17	-	32
	60	M16	-	-	-	37	2	-	12	32
	80	M8	M10	M12	33	-	2	17	-	26
	80	M16	-	-	-	39	2	-	12	26
	80	M20	-	-	-	39	2	-	15	26
	80	M24	-	-	-	41	2	-	19	26
	100	M8	M10	M12	35	-	2	17	-	22
	100	M16	-	-	-	41	2	-	12	22
	100	M20	-	-	-	41	2	-	15	22
	100	M24	-	-	-	43	2	-	19	22
	120	M20	-	-	-	43	2	-	15	20
	120	M24	-	-	-	46	2	-	19	20

**SP. 特長**

- 適用於侵蝕性環境
- 底板的傾斜表面有利於排水，有助於簡化清潔流程，並防止灰塵污垢的積聚
- 符合FDA標準的橡膠襯墊將底座密封可用於食品加工領域或製藥行業
- 螺帽規範：ISO 4032

**PS. 備註**

- 腳座出廠時已裝配好，不能拆卸

TYPE	d <sub>1</sub>	d <sub>2</sub>	靜荷重 kN	
			S/SK	T/TK
GN18	60	M8	8	-
	60	M10	14	-
	60	M12	14	-
	60	M16	-	14
	80	M8	8	-
	80	M10	14	-
	80	M12	14	-
	80	M16	-	14
	80	M20	-	32
	80	M24	-	36
	100	M8	8	-
	100	M10	14	-
	100	M12	16	-
	100	M16	-	24
	100	M20	-	26
	100	M24	-	28
	120	M20	-	26
	120	M24	-	26