



ROSTFREI
Inox
Stainless
Steel

- 2 Type**
- A** Fixing holes parallel to plunger
 - B** Fixing holes vertical to plunger

d ₁	d ₂	d ₃	d ₄	d ₅	k ±0,1	l ₁	l ₂ ≈	l ₃	s	t
M 12 x 1,5	32	M 5	4,5	12,2	21	22	26,5	9	12	3
M 16 x 1,5	46	M 8	5,5	16,2	32	33	37	13	15	3
M 20 x 1,5	46	M 8	5,5	20,2	32	33	37	13	15	3

Specification

- Steel —
- Blackened
- Grub screw GN 913.3 with brass pad
- Stainless steel AISI 303 **NI**
- Grub screw GN 913.5 with brass pad
- *Stainless Steel Characteristics* → Page 2166
- RoHS

Information

Mounting blocks GN 612.1 simplify the mounting of indexing plungers (e.g. GN 817) as well as cam action indexing plungers GN 612, GN 712 and GN 712.1.

To position the plunger pin of an indexing plunger or cam action indexing plunger, they can also hold positioning bushings GN 412.2 / GN 412.4.

see also...

- *Positioning Bushings GN 412.2 / GN 412.4* → Page 954
- *Positioning Bushings with Ramping Cone GN 412.3 / GN 412.5* → Page 955

How to order (Steel)	1 d ₁
GN 612.1-M20x1,5-A	2 Type

How to order (Stainless steel)	1 d ₁
GN 612.1-M16x1,5-B-NI	2 Type
	3 Material

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9