



RoHS SUS ENW=28~75
(2孔)W=100~150
(6孔)

T	公差	材質
0.03	±0.002	SUS301
0.05		
0.07	±0.005	
0.08		
0.1	±0.01	
0.2		
0.3	±0.02	
0.5		

品號	W	L	ℓ	T	庫存
D-STS-A1	28	75	45	0.03 0.05 0.1 0.2	.
		100	50		.
		125	75		.
		150	100		.
	38	75	45		.
		100	50		.
		125	75		.
		150	100		.
	48	75	45	0.03 0.05 0.07 0.08 0.1 0.2 0.3 0.5	.
		100	50		.
		125	75		.
		150	100		.
		200	150		.
		200	150		.
		200	150		.
	58	75	45	0.03 0.05 0.1	.
		100	50		.
		125	75		.
		150	100		.
	75	75	25	0.03 0.05 0.07 0.08 0.1 0.2 0.3 0.5	.
		100	50		.
		125	75		.
		150	100		.
		200	150		.

品號	W	L	ℓ	ℓ ₁	T	庫存
D-STS-A1	100	100	50	50	0.03 0.05 0.07 0.08 0.1	.
		125	75			.
		150	100			.
		200	150			.
		250	200			.
	125	125	75			.
		150	100			.
		200	150			.
		250	200			.
		150	100	100	0.3 0.5	.
	150	200	150			.
		250	200			.
		300	250			.

訂貨：[品號] - [W] × [L] × [T] 交期：[1] 天
D-STS-A1 - 28 × 75 × 0.05

SP 特長

- 厚度公差嚴格控管
- 產品上標示厚度、長度和寬度，節省量測時間，作業效率提升