





WWU
WUU (不銹鋼)



TWU
TUU (不銹鋼)



Type	材質
WWU	SWP
TWU	
WUU	SUS304
TUU	

· 輕中荷重型 *符號僅限於WWU · WUU

品號	Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫 存	
				最大拉伸量 Fmax. mm	最大荷重 N			WWU	TWU TUU
2-10	WWU	15	0.28	4.0	2.45	0.49	0.49	·	·
15				6.7			0.29	·	·
20				10.0			0.20	·	·
25				13.3			0.15	·	·
30	15.3	0.13	·	·					
3-10	WWU	15	0.35	4.6	3.33	0.66	0.59	·	·
15				9.1			0.29	·	·
20				14.3			0.19	·	·
25				19.5			0.14	·	·
30	24.8	0.11	·	·					
4-15	WWU	20	0.45	7.5	4.81	0.98	0.51	·	·
20				12.2			0.31	·	·
25				16.9			0.23	·	·
30				21.7			0.18	·	·
35	26.0	0.15	·	·					
40	30.0	0.13	·	·					
5-15	WWU	25	0.55	5.7	6.37	1.37	0.89	·	·
20				9.8			0.51	·	·
25				14.2			0.35	·	·
30				18.9			0.26	·	·
35	24.3	0.21	·	·					
40	28.3	0.18	·	·					
45	31.9	0.16	·	·					
50	36.4	0.14	·	·					
6-20	WWU	30	0.7	9.6	12.94	1.67	1.18	·	·
25				14.4			0.78	·	·
30				20.2			0.56	·	·
35				28.8			0.39	·	·
40	30.3	0.37	·	·					
45	34.8	0.32	·	·					
50	41.1	0.27	·	·					
55	44.2	0.25	·	·					
60	50.0	0.23	·	·					
8-25	WWU	35	0.9	10.0	18.63	3.92	1.47	·	·
30				14.3			1.03	·	·
35				18.8			0.78	·	·
40				23.8			0.62	·	·
45	28.3	0.52	·	·					
50	32.6	0.45	·	·					
55	37.5	0.39	·	·					
60	41.7	0.35	·	·					
65	46.9	0.31	·	·					
70	50.0	0.29	·	·					
10-30	WWU	40	1.1	9.9	23.24	4.71	1.87	·	·
35				14.0			1.32	·	·
40				18.0			1.03	·	·
45				22.2			0.83	·	·
50	26.3	0.71	·	·					
55	31.5	0.59	·	·					
60	35.7	0.52	·	·					
65	38.6	0.48	·	·					
70	43.0	0.43	·	·					
75	47.3	0.39	·	·					
80	51.0	0.36	·	·					
*符號僅限WWU	*90	59.0	0.31	·	-				
WUU	*100	67.5	0.27	·	-				

品號	Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫 存	
				最大拉伸量 Fmax. mm	最大荷重 N			WWU	TWU TUU
12-35	WWU	40	1.4	11.7	47.7	10.49	3.14	·	·
40				15.5			2.35	·	·
45				19.6			1.86	·	·
50				23.3			1.57	·	·
55				28.7			1.27	·	·
60				32.4			1.13	·	·
65				37.3			0.98	·	·
70				41.4			0.88	·	·
75				44.9			0.81	·	·
80				49.7			0.74	·	·
90	57.4	0.64	·	·					
100	65.4	0.56	·	·					
14-40	WWU	45	1.6	12.8	58.84	13.73	3.53	·	·
45				16.7			2.7	·	·
50				21.0			2.16	·	·
55				25.5			1.77	·	·
60				28.7			1.57	·	·
65				32.8			1.37	·	·
70				38.3			1.18	·	·
75				41.8			1.08	·	·
80				46.0			0.98	·	·
90				54.1			0.83	·	·
100	61.3	0.74	·	·					
125	83.6	0.54	·	·					
16-45	WWU	50	1.8 (WUU)	13.7	70.61	16.67	3.92	·	·
50				17.7			3.04	·	·
55				22.0			2.45	·	·
60				26.0			2.06	·	·
65				30.5			1.77	·	·
70			34.3	1.57			·	·	
75			39.2	1.37			·	·	
80			42.3	1.27			·	·	
90			50.0	1.08			·	·	
100			57.8	0.93			·	·	
125	78.7	0.69	·	·					
150	100.0	0.54	·	·					
18-50	WWU	55	2.0	14.7	81.39	17.65	4.34	·	-
55				19.1			3.34	·	·
60				23.2			2.75	·	·
65				27.0			2.36	·	·
70				30.9			2.06	·	·
75				36.1			1.77	·	·
80				40.6			1.57	·	·
90				48.1			1.33	·	·
100				56.5			1.13	·	·
125				76.4			0.83	·	·
150	100.0	0.64	·	·					
20-60	WWU	70	2.3	16.0	98.07	22.56	4.72	·	-
70				22.6			3.34	·	·
80				28.5			2.65	·	·
90				36.6			2.06	·	·
100				42.7			1.77	·	·
125				59.2			1.28	·	·
150				77.0			0.98	·	·
175				90.5			0.83	·	·



· 拉伸彈簧支柱溝槽型TSPO/STSP0, 圓孔型WSPO/SWSP0
WIPO/SWIPO詳細規格, 請至伍全官網

訂貨: 交期: 天

WWU2-10