



RoHS SUS



WWT
WUT (不銹鋼)



TWT
TUT (不銹鋼)



Type	材質
WWT TWT	SWP
WUT TUT	SUS304

· 重荷重型 *符號僅限於WWT · WUT

品號	Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫存		品號	Type	D-L	線徑 d	動荷重的情況		初張力 N	定數 N/mm	庫存						
				最大 拉伸量 Fmax. mm	最大 荷重 N			WWT WUT	TWT TUT					最大 拉伸量 Fmax. mm	最大 荷重 N			WWT WUT	TWT TUT					
WWT TWT WUT TUT		3-10 15 20 25	0.5	2.0 3.7 5.2 6.8	8.8	2.16	3.24 1.77 1.27 0.98	·	·	WWT TWT WUT TUT		12-65 70	2.0	13.1 14.9	120.62	34.3	6.57 5.79	·	·					
		*30		8.5				2.16	0.78		·	-						80	17.6	4.9	·	·		
		4-15		4.0				2.16	0.78		·	·						*90	19.1	4.52	·	·		
		20		6.4				1.37	·		·	·						*100	22.0	3.92	·	-		
		25		8.4				0.98	·		·	·												
WWT TWT WUT TUT		25 30	0.6	8.4 10.9	11.1	2.55	0.98	·	·	WWT TWT WUT TUT		14-40	2.3	5.8	154.95	45.11	19.02	·	·					
		*35		12.4			0.69	·	-								45	7.0	15.59	·	·			
		40		15.0			0.57	·	·		·						50	8.4	13.14	·	·			
		5-15		2.9			5.39	·	·		·						55	9.6	11.47	·	·			
		20		4.6			3.43	·	·		·						60	10.9	10.10	·	·			
WWT TWT WUT TUT		25 30	0.8	6.4 8.4	20.79	5.1	2.45	·	·	WWT TWT WUT TUT		65	2.3	12.9	154.95	45.11	8.53	·	-					
		*40		11.4			1.38	·	·		·						70	14.2	7.75	·	·			
		45		13.3			1.18	·	-		·						75	15.3	7.16	·	·			
		50		15.2			1.03	·	·		·						80	16.7	6.57	·	·			
		6-20		3.7			6.57	·	·		·						90	18.6	5.91	·	·			
WWT TWT WUT TUT		25 30	1.0	5.3 6.9	33.15	8.6	4.61	·	·	WWT TWT WUT TUT		100	2.6	21.1	195.15	55.9	5.21	·	·					
		*45		10.8			1.71	·	-		·						125	28.0	3.92	·	·			
		50		12.5			1.96	·	·		·						16-50	7.5	18.63	·	·			
		*55		14.3			1.57	·	·		·						55	9.0	15.49	·	·			
		60		15.6			1.57	·	·		·						60	10.4	13.34	·	·			
WWT TWT WUT TUT		35 40	1.2	8.3 10.0	41.19	9.81	2.94	·	·	WWT TWT WUT TUT		65	2.6	11.9	195.15	55.9	11.67	·	·					
		*50		12.5			1.96	·	·		·						70	13.4	10.40	·	·			
		55		14.3			1.71	·	-		·						75	15.0	9.32	·	-			
		*60		15.6			1.57	·	·		·						80	16.5	8.43	·	·			
		8-25		5.3			5.88	·	·		·						90	19.4	7.16	·	·			
WWT TWT WUT TUT		30 35	1.2	7.3 9.1	41.19	9.81	4.31	·	·	WWT TWT WUT TUT		100	2.9	22.4	236.34	68.65	6.18	·	·					
		*65		18.8			1.52	·	-		·						125	28.4	4.90	·	·			
		70		22.8			1.38	·	·		·						150	35.5	3.92	·	·			
		10-30		5.2			10.89	·	·		·						18-55	8.3	20.10	·	·			
		35		6.8			8.34	·	·		·						60	10.0	16.67	·	·			
WWT TWT WUT TUT		40 45	1.6	8.4 10.0	77.47	20.59	6.77	·	·	WWT TWT WUT TUT		65	3.2	11.6	281.45	82.38	14.71	·	·					
		*70		18.8			1.67	·	-		·						70	12.5	13.44	·	·			
		50		11.6			4.9	·	·		·						75	14.1	11.77	·	·			
		55		13.2			4.31	·	·		·						80	15.8	10.79	·	·			
		*65		17.0			3.35	·	·		·						90	18.4	9.12	·	-			
WWT TWT WUT TUT		60 *75	2.0	15.2 17.0	120.62	34.3	3.73	·	·	WWT TWT WUT TUT		100	4.0	21.6	430.51	123.6	7.75	·	·					
		*80		20.7			2.75	·	-		·						125	27.1	6.19	·	·			
		75		24.1			2.36	·	·		·						150	34.2	4.90	·	·			
		*90		26.3			1.96	·	·		·						20-60	9.2	21.57	·	·			
		80		29.0			1.38	·	·		·						70	11.9	16.67	·	·			
WWT TWT WUT TUT		45 50	2.0	7.7 9.4	120.62	34.3	11.18	·	·	WWT TWT WUT TUT		80	4.0	14.7	430.51	123.6	13.53	·	·					
		*55		10.5			9.22	·	·		·						90	17.5	11.38	·	·			
		55		12.1			8.24	·	·		·						100	20.1	9.9	·	·			
		60		12.1			7.16	·	·		·						125	27.8	7.16	·	-			
		12-40		6.6			13.04	·	·		·						150	33.8	5.89	·	·			
WWT TWT WUT TUT		45 50	2.0	7.7 9.4	120.62	34.3	11.18	·	·	WWT TWT WUT TUT		175	4.0	40.5	430.51	123.6	4.90	·	·					
		*55		10.5			9.22	·	·		·						24-80	11.7	26.48	·	·			
		55		12.1			8.24	·	·		·						90	13.7	22.46	·	·			
		60		12.1			7.16	·	·		·						100	16.6	18.63	·	·			
		12-40		6.6			13.04	·	·		·						125	22.5	13.53	·	-			
WWT TWT WUT TUT		45 50	2.0	7.7 9.4	120.62	34.3	11.18	·	·	WWT TWT WUT TUT		150	4.0	28.5	430.51	123.6	10.79	·	·					
		*55		10.5			9.22	·	·		·						175	34.4	8.92	·	·			
		55		12.1			8.24	·	·		·						200	41.2	7.45	·	·			
		60		12.1			7.16	·	·		·													
		12-40		6.6			13.04	·	·		·													

訂貨： 交期： 天

備註 · 拉伸彈簧支柱溝槽型TSPO/STSP0，圓孔型WSPO/SWSP0
WIPO/SWIPO詳細規格，請至伍全官網

WWT3-10