



TR					
外徑D	內徑d	自由長		荷重	旋向
		50mm以下	55mm以上		
+0 -1.2	+1.2 -0	±0.5	±2%	±10%	右

材質	顏色
砂銻合金鋼	銀

品號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫存			
Type	D - L	外徑 mm	內徑 mm	自由長 mm	N/mm	壓縮量 mm	荷重 N	壓縮量 mm	荷重 N	壓縮量 mm	荷重 N				
TR	14.5-020	14.5	9	20	10.90	88.3	8	9.0	98.1	10.0	107.9	•			
	025			25	8.72							10	11.3	12.5	•
	030			30	7.27							12	13.5	15.0	•
	035			35	6.23							14	15.8	17.5	•
	040			40	5.45							16	18.0	20.0	•
	045			45	4.84							18	20.3	22.5	•
	050			50	4.36							20	22.5	25.0	•
	055			55	3.96							22	24.8	27.5	•
	060			60	3.63							24	27.0	30.0	•
	065			65	3.35							26	29.3	32.5	•
	070			70	3.11							28	31.5	35.0	•
	075			75	2.91							30	33.8	37.5	•
	080			80	2.73							32	36.0	40.0	•
	090			90	2.42							36	40.5	45.0	•
100	100	2.18	40	45.0	50.0	•									
125	125	1.74	50	56.3	62.5	•									
TR	17-025	17	11	25	14.82	147.1	10	11.3	166.7	12.5	186.3	•			
	030			30	12.35							12	13.5	15.0	•
	035			35	10.58							14	15.8	17.5	•
	040			40	9.26							16	18.0	20.0	•
	045			45	8.23							18	20.3	22.5	•
	050			50	7.41							20	22.5	25.0	•
	055			55	6.74							22	24.8	27.5	•
	060			60	6.17							24	27.0	30.0	•
	065			65	5.70							26	29.3	32.5	•
	070			70	5.29							28	31.5	35.0	•
	075			75	4.94							30	33.8	37.5	•
	080			80	4.63							32	36.0	40.0	•
	090			90	4.12							36	40.5	45.0	•
	100			100	3.70							40	45.0	50.0	•
125	125	2.96	50	56.3	62.5	•									
150	150	2.47	60	67.5	75.0	•									
TR	21-030	21	13	30	13.80	166.7	12	13.5	186.3	15.0	205.9	•			
	035			35	11.83							14	15.8	17.5	•
	040			40	10.35							16	18.0	20.0	•
	045			45	9.20							18	20.3	22.5	•
	050			50	8.28							20	22.5	25.0	•
	055			55	7.53							22	24.8	27.5	•
	060			60	6.90							24	27.0	30.0	•
	065			65	6.37							26	29.3	32.5	•
	070			70	5.91							28	31.5	35.0	•
	075			75	5.52							30	33.8	37.5	•
	080			80	5.18							32	36.0	40.0	•
	090			90	4.60							36	40.5	45.0	•
	100			100	4.14							40	45.0	50.0	•
	125			125	3.31							50	56.3	62.5	•
150	150	2.76	60	67.5	75.0	•									

使用回數	100萬回	50萬回	30萬回
------	-------	------	------

品 號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫 存						
Type	D - L	外徑 mm	內徑 mm	自由長 mm	N/ mm	壓縮量 mm	荷重 N	壓縮量 mm	荷重 N	壓縮量 mm	荷重 N							
TR	26-030	26	16.5	30	26.87	12	323.6	13.5	362.8	15.0	402.1	・						
	035			35	23.03	14		15.8		17.5		・						
	040			40	20.16	16		18.0		20.0		・						
	045			45	17.92	18		20.3		22.5		・						
	050			50	16.12	20		22.5		25.0		・						
	055			55	14.66	22		24.8		27.5		・						
	060			60	13.44	24		27.0		30.0		・						
	065			65	12.40	26		29.3		32.5		・						
	070			70	11.52	28		31.5		35.0		・						
	075			75	10.75	30		33.8		37.5		・						
	080			80	10.08	32		36.0		40.0		・						
	090			90	8.96	36		40.5		45.0		・						
	100			100	8.06	40		45.0		50.0		・						
	110			110	7.33	44		49.5		55.0		・						
	125			125	6.45	50		56.3		62.5		・						
	150			150	5.37	60		67.5		75.0		・						
	175			175	4.61	70		78.8		87.5		・						
200	200	4.03	80	90.0	100.0	・												
TR	32-040	32	21	40	25.06	16	402.1	18.0	451.1	20.0	500.1	・						
	045			45	22.28	18		20.3		22.5		・						
	050			50	20.05	20		22.5		25.0		・						
	060			60	16.71	24		27.0		30.0		・						
	070			70	14.32	28		31.5		35.0		・						
	080			80	12.53	32		36.0		40.0		・						
	090			90	11.14	36		40.5		45.0		・						
	100			100	10.02	40		45.0		50.0		・						
	110			110	9.11	44		49.5		55.0		・						
	125			125	8.02	50		56.3		62.5		・						
	150			150	6.68	60		67.5		75.0		・						
	175			175	5.73	70		78.8		87.5		・						
	200			200	5.01	80		90.0		100.0		・						
	250			250	4.01	100		112.5		125.0		・						
	300			300	3.34	120		135.0		150.0		・						
	TR			39-040	39	26		40		27.24		16	431.5	18.0	490.3	20.0	539.4	・
				045				45		24.21		18		20.3		22.5		・
050		50	21.79	20			22.5	25.0	・									
060		60	18.16	24			27.0	30.0	・									
070		70	15.57	28			31.5	35.0	・									
080		80	13.62	32			36.0	40.0	・									
090		90	12.11	36			40.5	45.0	・									
100		100	10.90	40			45.0	50.0	・									
110		110	9.91	44			49.5	55.0	・									
125		125	8.72	50			56.3	62.5	・									
150		150	7.26	60			67.5	75.0	・									
175		175	6.23	70			78.8	87.5	・									
200		200	5.45	80			90.0	100.0	・									
250		250	4.36	100			112.5	125.0	・									
300		300	3.63	120			135.0	150.0	・									
TR		46-050	46	32			50	24.41	20	490.3	22.5	549.2		25.0		608.0		・
		060					60	20.34	24		27.0			30.0				・
	070	70			17.43	28	31.5	35.0	・									
	080	80			15.26	32	36.0	40.0	・									
	090	90			13.56	36	40.5	45.0	・									
	100	100			12.20	40	45.0	50.0	・									
	110	110			11.09	44	49.5	55.0	・									
	125	125			9.76	50	56.3	62.5	・									
	150	150			8.14	60	67.5	75.0	・									
	175	175			6.97	70	78.8	87.5	・									
	200	200			6.10	80	90.0	100.0	・									
	250	250			4.88	100	112.5	125.0	・									
	300	300			4.07	120	135.0	150.0	・									

使用回數

100萬回

50萬回

30萬回

## PS. 備註

- ・荷重(N)=定數(N/mm)×壓縮量(mm)
- ・耐熱溫度150°C，最適合塑膠模使用
- ・1N=0.101972 kgf

訂貨：  交期：  天

TR26-030