


RoHS



TY					
外徑D	內徑d	自由長		荷重	旋向
		50mm以下	55mm以上		
+0 -1.2	+1.2 -0	±0.5	±2%	±10%	右

材質	顏色
矽鉻合金鋼	紫

品號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫存			
Type	D - L	外徑 mm	內徑 mm	自由長 mm	N/mm	壓縮量 荷重		壓縮量 荷重		壓縮量 荷重					
						mm	N	mm	N	mm	N				
TY	14.5-020	14.5	9	20	18.52	147.1	8	166.7	9.0	166.7	186.3	10.0			
	025			25	14.82								10	11.3	12.5
	030			30	12.35								12	13.5	15.0
	035			35	10.58								14	15.8	17.5
	040			40	9.26								16	18.0	20.0
	045			45	8.23								18	20.3	22.5
	050			50	7.41								20	22.5	25.0
	055			55	6.74								22	24.8	27.5
	060			60	6.17								24	27.0	30.0
	065			65	5.70								26	29.3	32.5
	070			70	5.29								28	31.5	35.0
	075			75	4.94								30	33.8	37.5
	080			80	4.63								32	36.0	40.0
	090			90	4.12								36	40.5	45.0
	100			100	3.70								40	45.0	50.0
125	125	2.96	50	56.3	62.5										
TY	17-025	17	11	25	21.80	215.7	10	245.2	11.3	245.2	274.6	12.5			
	030			30	18.16								12	13.5	15.0
	035			35	15.57								14	15.8	17.5
	040			40	13.62								16	18.0	20.0
	045			45	12.11								18	20.3	22.5
	050			50	10.90								20	22.5	25.0
	055			55	9.91								22	24.8	27.5
	060			60	9.08								24	27.0	30.0
	065			65	8.38								26	29.3	32.5
	070			70	7.78								28	31.5	35.0
	075			75	7.27								30	33.8	37.5
	080			80	6.81								32	36.0	40.0
	090			90	6.05								36	40.5	45.0
	100			100	5.45								40	45.0	50.0
	125			125	4.36								50	56.3	62.5
150	150	3.63	60	67.5	75.0										
TY	21-030	21	13	30	23.24	284.4	12	313.8	13.5	313.8	353.0	15.0			
	035			35	19.92								14	15.8	17.5
	040			40	17.43								16	18.0	20.0
	045			45	15.50								18	20.3	22.5
	050			50	13.95								20	22.5	25.0
	055			55	12.68								22	24.8	27.5
	060			60	11.62								24	27.0	30.0
	065			65	10.73								26	29.3	32.5
	070			70	9.96								28	31.5	35.0
	075			75	9.30								30	33.8	37.5
	080			80	8.72								32	36.0	40.0
	090			90	7.75								36	40.5	45.0
	100			100	6.97								40	45.0	50.0
	125			125	5.58								50	56.3	62.5
	150			150	4.65								60	67.5	75.0
使用回數						100萬回	50萬回	30萬回							

品 號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫 存									
Type	D - L	外徑	內徑	自由長	N/mm	壓縮量	荷重	壓縮量	荷重	壓縮量	荷重										
		mm	mm	mm		mm	N	mm	N	mm	N										
TY	26-030	26	16.5	30	34.87	411.9	12	13.5	470.7	15.0	519.8	•									
	035			35	29.89							14	15.8	17.5	•						
	040			40	26.15							16	18.0	20.0	•						
	045			45	23.24							18	20.3	22.5	•						
	050			50	20.92							20	22.5	25.0	•						
	055			55	19.02							22	24.8	27.5	•						
	060			60	17.43							24	27.0	30.0	•						
	065			65	16.09							26	29.3	32.5	•						
	070			70	14.94							28	31.5	35.0	•						
	075			75	13.95							30	33.8	37.5	•						
	080			80	13.08							32	36.0	40.0	•						
	090			90	11.62							36	40.5	45.0	•						
	100			100	10.46							40	45.0	50.0	•						
	110			110	9.51							44	49.5	55.0	•						
	125			125	8.37							50	56.3	62.5	•						
	150			150	6.97							60	67.5	75.0	•						
	175			175	5.98							70	78.8	87.5	•						
200	200	5.23	80	90.0	100.0	•															
TY	32-040	32	21	40	34.87	559.0	16	18.0	627.6	20.0	696.3	•									
	045			45	30.99							18	20.3	22.5	•						
	050			50	27.89							20	22.5	25.0	•						
	060			60	23.24							24	27.0	30.0	•						
	070			70	19.92							28	31.5	35.0	•						
	080			80	17.43							32	36.0	40.0	•						
	090			90	15.50							36	40.5	45.0	•						
	100			100	13.95							40	45.0	50.0	•						
	110			110	12.68							44	49.5	55.0	•						
	125			125	11.16							50	56.3	62.5	•						
	150			150	9.30							60	67.5	75.0	•						
	175			175	9.97							70	78.8	87.5	•						
	200			200	6.97							80	90.0	100.0	•						
	250			250	5.58							100	112.5	125.0	•						
	300			300	4.65							120	135.0	150.0	•						
	TY			39-040	39							26	40	45.77	725.7	16	18.0	823.8	20.0	912.0	•
				045									45	40.68							18
050		50	36.61	20		22.5	25.0	•													
060		60	30.51	24		27.0	30.0	•													
070		70	26.15	28		31.5	35.0	•													
080		80	22.88	32		36.0	40.0	•													
090		90	20.34	36		40.5	45.0	•													
100		100	18.31	40		45.0	50.0	•													
110		110	16.64	44		49.5	55.0	•													
125		125	14.65	50		56.3	62.5	•													
150		150	12.20	60		67.5	75.0	•													
175		175	10.46	70		78.8	87.5	•													
200		200	9.15	80		90.0	100.0	•													
250		250	7.32	100		112.5	125.0	•													
300		300	6.10	120		135.0	150.0	•													
TY		46-050	46	32		50	48.81	970.9	20	22.5	1098		25.0	1216.0							•
		060				60	40.68														24
	070	70			34.87	28	31.5					35.0			•						
	080	80			30.51	32	36.0					40.0			•						
	090	90			27.12	36	40.5					45.0			•						
	100	100			24.41	40	45.0					50.0			•						
	110	110			22.19	44	49.5					55.0			•						
	125	125			19.53	50	56.3					62.5			•						
	150	150			16.27	60	67.5					75.0			•						
	175	175			13.95	70	78.8					87.5			•						
	200	200			12.20	80	90.0					100.0			•						
	250	250			9.76	100	112.5					125.0			•						
	300	300			8.14	120	135.0					150.0			•						

使用回數

100萬回

50萬回

30萬回

## PS. 備註

- ・荷重(N)=定數(N/mm)×壓縮量(mm)
- ・耐熱溫度150°C，最適合塑膠模使用
- ・1N=0.101972 kgf

訂貨：  交期：  天

TY26-030