


RoHS



TY					
外徑D	內徑d	自由長		荷重	旋向
		50mm以下	55mm以上		
+0 -1.2	+1.2 -0	±0.5	±2%	±10%	右

材質	顏色
SWOSC-V	紫

品號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫存
Type	D - L	外徑 mm	內徑 mm	自由長 mm	N/mm	壓縮量	荷重	壓縮量	荷重	壓縮量	荷重	
						mm	N	mm	N	mm	N	
TY	14.5-020	14.5	9	20	18.52	8	147.1	9.0	166.7	10.0	186.3	•
	025			25	14.82	10		11.3		12.5		•
	030			30	12.35	12		13.5		15.0		•
	035			35	10.58	14		15.8		17.5		•
	040			40	9.26	16		18.0		20.0		•
	045			45	8.23	18		20.3		22.5		•
	050			50	7.41	20		22.5		25.0		•
	055			55	6.74	22		24.8		27.5		•
	060			60	6.17	24		27.0		30.0		•
	065			65	5.70	26		29.3		32.5		•
	070			70	5.29	28		31.5		35.0		•
	075			75	4.94	30		33.8		37.5		•
	080			80	4.63	32		36.0		40.0		•
	090			90	4.12	36		40.5		45.0		•
	100			100	3.70	40		45.0		50.0		•
125	125	2.96	50	56.3	62.5	•						
TY	17-025	17	11	25	21.80	10	215.7	11.3	245.2	12.5	274.6	•
	030			30	18.16	12		13.5		15.0		•
	035			35	15.57	14		15.8		17.5		•
	040			40	13.62	16		18.0		20.0		•
	045			45	12.11	18		20.3		22.5		•
	050			50	10.90	20		22.5		25.0		•
	055			55	9.91	22		24.8		27.5		•
	060			60	9.08	24		27.0		30.0		•
	065			65	8.38	26		29.3		32.5		•
	070			70	7.78	28		31.5		35.0		•
	075			75	7.27	30		33.8		37.5		•
	080			80	6.81	32		36.0		40.0		•
	090			90	6.05	36		40.5		45.0		•
	100			100	5.45	40		45.0		50.0		•
	125			125	4.36	50		56.3		62.5		•
150	150	3.63	60	67.5	75.0	•						
TY	21-030	21	13	30	23.24	12	284.4	13.5	313.8	15.0	353.0	•
	035			35	19.92	14		15.8		17.5		•
	040			40	17.43	16		18.0		20.0		•
	045			45	15.50	18		20.3		22.5		•
	050			50	13.95	20		22.5		25.0		•
	055			55	12.68	22		24.8		27.5		•
	060			60	11.62	24		27.0		30.0		•
	065			65	10.73	26		29.3		32.5		•
	070			70	9.96	28		31.5		35.0		•
	075			75	9.30	30		33.8		37.5		•
	080			80	8.72	32		36.0		40.0		•
	090			90	7.75	36		40.5		45.0		•
	100			100	6.97	40		45.0		50.0		•
	125			125	5.58	50		56.3		62.5		•
	150			150	4.65	60		67.5		75.0		•
使用回數						100萬回	50萬回	30萬回				

品 號		D	d	L	定數	F=L×40%		F=L×45%		F=L×50%		庫 存									
Type	D - L	外徑 mm	內徑 mm	自由長 mm	N/mm	壓縮量	荷重	壓縮量	荷重	壓縮量	荷重										
						mm	N	mm	N	mm	N										
TY	26-030	26	16.5	30	34.87	411.9	12	13.5	470.7	15.0	519.8	•									
	035			35	29.89							14	15.8	17.5	•						
	040			40	26.15							16	18.0	20.0	•						
	045			45	23.24							18	20.3	22.5	•						
	050			50	20.92							20	22.5	25.0	•						
	055			55	19.02							22	24.8	27.5	•						
	060			60	17.43							24	27.0	30.0	•						
	065			65	16.09							26	29.3	32.5	•						
	070			70	14.94							28	31.5	35.0	•						
	075			75	13.95							30	33.8	37.5	•						
	080			80	13.08							32	36.0	40.0	•						
	090			90	11.62							36	40.5	45.0	•						
	100			100	10.46							40	45.0	50.0	•						
	110			110	9.51							44	49.5	55.0	•						
	125			125	8.37							50	56.3	62.5	•						
	150			150	6.97							60	67.5	75.0	•						
	175			175	5.98							70	78.8	87.5	•						
200	200	5.23	80	90.0	100.0	•															
TY	32-040	32	21	40	34.87	559.0	16	18.0	627.6	20.0	696.3	•									
	045			45	30.99							18	20.3	22.5	•						
	050			50	27.89							20	22.5	25.0	•						
	060			60	23.24							24	27.0	30.0	•						
	070			70	19.92							28	31.5	35.0	•						
	080			80	17.43							32	36.0	40.0	•						
	090			90	15.50							36	40.5	45.0	•						
	100			100	13.95							40	45.0	50.0	•						
	110			110	12.68							44	49.5	55.0	•						
	125			125	11.16							50	56.3	62.5	•						
	150			150	9.30							60	67.5	75.0	•						
	175			175	9.97							70	78.8	87.5	•						
	200			200	6.97							80	90.0	100.0	•						
	250			250	5.58							100	112.5	125.0	•						
	300			300	4.65							120	135.0	150.0	•						
	TY			39-040	39							26	40	45.77	725.7	16	18.0	823.8	20.0	912.0	•
				045									45	40.68							18
050		50	36.61	20		22.5	25.0	•													
060		60	30.51	24		27.0	30.0	•													
070		70	26.15	28		31.5	35.0	•													
080		80	22.88	32		36.0	40.0	•													
090		90	20.34	36		40.5	45.0	•													
100		100	18.31	40		45.0	50.0	•													
110		110	16.64	44		49.5	55.0	•													
125		125	14.65	50		56.3	62.5	•													
150		150	12.20	60		67.5	75.0	•													
175		175	10.46	70		78.8	87.5	•													
200		200	9.15	80		90.0	100.0	•													
250		250	7.32	100		112.5	125.0	•													
300		300	6.10	120		135.0	150.0	•													
TY		46-050	46	32		50	48.81	970.9	20	22.5	1098		25.0	1216.0							•
		060				60	40.68														24
	070	70			34.87	28	31.5					35.0			•						
	080	80			30.51	32	36.0					40.0			•						
	090	90			27.12	36	40.5					45.0			•						
	100	100			24.41	40	45.0					50.0			•						
	110	110			22.19	44	49.5					55.0			•						
	125	125			19.53	50	56.3					62.5			•						
	150	150			16.27	60	67.5					75.0			•						
	175	175			13.95	70	78.8					87.5			•						
	200	200			12.20	80	90.0					100.0			•						
	250	250			9.76	100	112.5					125.0			•						
	300	300			8.14	120	135.0					150.0			•						

使用回數

100萬回

50萬回

30萬回

PS 備註

- ・荷重(N)=定數(N/mm)×壓縮量(mm)
- ・耐熱溫度150°C，最適合塑膠模使用
- ・1N=0.101972 kgf

訂貨： 交期： 天

TY26-030