


 AAU・AAV  
 固定圈  
 (請參考P.414)

材質	硬度	顏色
PU	蕭氏 A90	黑

品 號			F=L×15%		F=L×20%		F=L×25%		V	d	庫存
			壓縮量	荷重	壓縮量	荷重	壓縮量	荷重			
TYPE	D	L	mm	N	mm	N	mm	N			
AA	15	25	3.8	588	5	785	6.3	981	18	7.0	•
		30	4.5		6		7.5				•
		35	5.3		7		8.8				•
		40	6.0		8		10.0				•
	20	25	3.8	1128	5	1422	6.3	1765	24	8.5	•
		30	4.5		6		7.5				•
		35	5.3		7		8.8				•
		40	6.0		8		10.0				•
	25	25	3.8	1667	5	2157	6.3	2648	30	11.0	•
		30	4.5		6		7.5				•
		35	5.3		7		8.8				•
		40	6.0		8		10.0				•
		45	6.8		9		11.3				•
	30	25	3.8	2599	5	3040	6.3	3531	37	14.0	•
		30	4.5		6		7.5				•
		35	5.3		7		8.8				•
		40	6.0		8		10.0				•
		45	6.8		9		11.3				•
		50	7.5		10		12.5				•
		55	8.3		11		13.8				•
	40	40	6.0	4560	8	5394	10.0	6276	48	14.0	•
		50	7.5		10		12.5				•
		60	9.0		12		15.0				•
		80	12.0		16		20.0				•
	50	50	7.5	7747	10	9218	12.5	10787	60	14.0	•
		60	9.0		12		15.0				•
		80	12.0		16		20.0				•
	60	50	7.5	13042	10	15102	12.5	17652	72	14.0	•
		60	9.0		12		15.0				•
		80	12.0		16		20.0				•
	80	60	9.0	21378	12	25399	15.0	29420	95	22.0	•
		80	12.0		16		20.0				•
		100	15.0		20		25.0				•
	100	80	12.0	35990	16	42659	20.0	49720	119	22.0	•
		100	15.0		20		25.0				•
		120	18.0		24		30.0				•

**Wa. 注意**

- ・優力膠在高溫或陽光直接照射的環境下將會造成品質特性低劣的情況發生
- ・特殊材質、硬度、尺寸歡迎洽詢

 訂貨：  交期：  天

AA40-40