



**Rost**  
**frei** | Inox  
Stainless  
Steel

**3 Type**

- A** Without knurl
- B** With knurl

**1**

**2**

<b>d<sub>1</sub></b>	<b>d<sub>2</sub></b>	<b>d<sub>3</sub></b>	<b>h<sub>1</sub></b>	<b>h<sub>2</sub></b>	<b>t</b> min.
21	M 4	12,5	18	10,5	10
21	M 5	12,5	18	10,5	10
25	M 6	14,5	22,5	14	12
25	M 8	14,5	22,5	14	12
31	M 8	18,5	27	17	15
31	M 10	18,5	27	17	17

**Specification**

- **GN 676.2**  
Steel  
Zinc plated, blue passivated
- *Stainless Steel Characteristics* → Page 2166
- **RoHS**

**Information**

Knobs GN 676.2 are used in applications where a push or pull movement is required. Their concave top gives a more comfortable thumb grip.

The version with knurl (type B) can be used as a knurled nut.

see also...

- *Knurled Knobs GN 676 (Plastic)* → Page 84
- *Knurled Knobs GN 676 (Plastic, Detectable)* → Page 86
- *Knurled Knobs GN 676 (Plastic, Antibacterial)* → Page 87
- *Waist Shaped Knobs GN 75 (Steel)* → Page 82
- *Waist Shaped Knobs GN 75.5 (Stainless Steel)* → Page 82

How to order (Steel, zinc plated)

**GN 676.2-25-M6-B**

- 1** d<sub>1</sub>
- 2** d<sub>2</sub>
- 3** Type