

鏈條 DIN 8187		TC-CV					TC-BC			庫存		
ISO NO.	ANSI NO.	品號	Code	A	H	W	品號	Code	品號			
06B	-	TC-CV1S	BL010641	18	33	5	TC-BC-10X	BL010610	TC-BC10XCV1S	•		
									TC-BC-20X	BL010612	TC-BC20XCV1S	•
08B	40	TC-CV2S	BL010642					7	TC-BC-10X	BL010610	TC-BC10XCV2S	•
									TC-BC-20X	BL010612	TC-BC20XCV2S	•
10B	50	TC-CV3S	BL010643					9	TC-BC-30X	BL010614	TC-BC30XCV3S	•
									TC-BC-20X	BL010612	TC-BC20XCV4S	•
12B	60	TC-CV4S	BL010644				11	TC-BC-30X	BL010614	TC-BC30XCV4S	•	
06B	-	TC-CV1D	BL010651			33	5	TC-BC-10X	BL010610	TC-BC10XCV1D	•	
08B	40	TC-CV2D	BL010652		21	43	7	TC-BC-20X	BL010612	TC-BC20XCV1D	•	
											TC-BC20XCV2D	•
10B	50	TC-CV3D	BL010653		25		9			TC-BC20XCV3D	•	
										TC-BC30XCV3D	•	
12B	60	TC-CV4D	BL010654	30	33	11	TC-BC-30X	BL010614	TC-BC30XCV4D	•		


**Sp. 特長**

- 可使用在自動鏈條張力器，或衝擊吸收功能的機構
- 此產品可使鏈條的驅動正常，保持震動吸收，延長機器壽命
- 裝置簡單容易的預壓系統內藏

**Ps. 備註**


- 本體TC-BC和鏈條導板TC-CV，材質請參閱本單元

**Ex. 使用例**



**Te. 技術資料**

- 使用溫度：max.80°C
- 1N = 0.101972 Kgf



訂貨：  交期：

TC-BC10XCV1S