

底座		螺栓
材質	顏色	材質
PA+玻纖	藍	SUS304

品號	描述	D	d	d1	L	l	l1	d2	h	h1	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
185301	LV.F-80-14-SST-M8x43-VD	80	M8	54	76	43	33	8.5	24	23	14	14	16000	86	△
185303	LV.F-80-14-SST-M8x68-VD	80	M8	54	101	68	33	8.5	24	23	14	14	16000	98	△
185311	LV.F-80-14-SST-M10x43-VD	80	M10	54	76	43	33	8.5	24	23	14	14	16000	95	△
185313	LV.F-80-14-SST-M10x68-VD	80	M10	54	101	68	33	8.5	24	23	14	14	16000	108	△
185315	LV.F-80-14-SST-M10x98-VD	80	M10	54	131	98	33	8.5	24	23	14	14	16000	122	△
185321	LV.F-80-14-SST-M12x43-VD	80	M12	54	76	43	33	8.5	24	23	14	14	16000	105	△
185323	LV.F-80-14-SST-M12x68-VD	80	M12	54	101	68	33	8.5	24	23	14	14	16000	123	△
185325	LV.F-80-14-SST-M12x98-VD	80	M12	54	131	98	33	8.5	24	23	14	14	16000	145	△
185331	LV.F-80-14-SST-M14x68-VD	80	M14	54	101	68	33	8.5	24	23	14	14	16000	146	△
185333	LV.F-80-14-SST-M14x98-VD	80	M14	54	131	98	33	8.5	24	23	14	14	16000	167	△
185335	LV.F-80-14-SST-M14x148-VD	80	M14	54	181	148	33	8.5	24	23	14	14	16000	250	△
185341	LV.F-80-14-SST-M16x68-VD	80	M16	54	101	68	33	8.5	24	23	16	14	16000	168	△
185343	LV.F-80-14-SST-M16x108-VD	80	M16	54	141	108	33	8.5	24	23	16	14	16000	222	△
185345	LV.F-80-14-SST-M16x148-VD	80	M16	54	181	148	33	8.5	24	23	16	14	16000	275	△
185347	LV.F-80-14-SST-M16x168-VD	80	M16	54	201	168	33	8.5	24	23	16	14	16000	302	△
185351	LV.F-80-24-SST-M16x58-VD	80	M16	54	101	58	43	8.5	24	23	24	24	18000	230	△
185353	LV.F-80-24-SST-M16x98-VD	80	M16	54	141	98	43	8.5	24	23	24	24	18000	282	△
185355	LV.F-80-24-SST-M16x138-VD	80	M16	54	181	138	43	8.5	24	23	24	24	18000	333	△
185357	LV.F-80-24-SST-M16x158-VD	80	M16	54	201	158	43	8.5	24	23	24	24	18000	361	△
185361	LV.F-80-24-SST-M20x98-VD	80	M20	54	141	98	43	8.5	24	23	24	24	18000	354	△
185363	LV.F-80-24-SST-M20x138-VD	80	M20	54	181	138	43	8.5	24	23	24	24	18000	434	△
185365	LV.F-80-24-SST-M20x158-VD	80	M20	54	201	158	43	8.5	24	23	24	24	18000	474	△
185367	LV.F-80-24-SST-M20x198-VD	80	M20	54	241	198	43	8.5	24	23	24	24	18000	559	△
185371	LV.F-80-24-SST-M24x98-VD	80	M24	54	141	98	43	8.5	24	23	24	24	18000	454	△
185373	LV.F-80-24-SST-M24x158-VD	80	M24	54	201	158	43	8.5	24	23	24	24	18000	629	△
185375	LV.F-80-24-SST-M24x198-VD	80	M24	54	241	198	43	8.5	24	23	24	24	18000	750	△

品號	描述	D	d	d1	L	l	l1	d2	h	h1	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
185401	LV.F-100-14-SST-M8x43-VD	100	M8	70	76	43	33	12.5	24	23	14	14	18000	93	△
185403	LV.F-100-14-SST-M8x68-VD	100	M8	70	101	68	33	12.5	24	23	14	14	18000	105	△
185411	LV.F-100-14-SST-M10x43-VD	100	M10	70	76	43	33	12.5	24	23	14	14	18000	102	△
185413	LV.F-100-14-SST-M10x68-VD	100	M10	70	101	68	33	12.5	24	23	14	14	18000	114	△
185415	LV.F-100-14-SST-M10x98-VD	100	M10	70	131	98	33	12.5	24	23	14	14	18000	128	△
185421	LV.F-100-14-SST-M12x43-VD	100	M12	70	76	43	33	12.5	24	23	14	14	18000	112	△
185423	LV.F-100-14-SST-M12x68-VD	100	M12	70	101	68	33	12.5	24	23	14	14	18000	129	△
185425	LV.F-100-14-SST-M12x98-VD	100	M12	70	131	98	33	12.5	24	23	14	14	18000	150	△
185431	LV.F-100-14-SST-M14x68-VD	100	M14	70	101	68	33	12.5	24	23	14	14	18000	151	△
185433	LV.F-100-14-SST-M14x98-VD	100	M14	70	131	98	33	12.5	24	23	14	14	18000	172	△
185435	LV.F-100-14-SST-M14x148-VD	100	M14	70	181	148	33	12.5	24	23	14	14	18000	255	△
185441	LV.F-100-14-SST-M16x68-VD	100	M16	70	101	68	33	12.5	24	23	16	14	18000	173	△
185443	LV.F-100-14-SST-M16x108-VD	100	M16	70	141	108	33	12.5	24	23	16	14	18000	225	△
185445	LV.F-100-14-SST-M16x148-VD	100	M16	70	181	148	33	12.5	24	23	16	14	18000	277	△
185447	LV.F-100-14-SST-M16x168-VD	100	M16	70	201	168	33	12.5	24	23	16	14	18000	303	△
185451	LV.F-100-24-SST-M16x58-VD	100	M16	70	101	58	43	12.5	24	23	24	24	25000	260	△
185453	LV.F-100-24-SST-M16x98-VD	100	M16	70	141	98	43	12.5	24	23	24	24	25000	312	△
185455	LV.F-100-24-SST-M16x138-VD	100	M16	70	181	138	43	12.5	24	23	24	24	25000	363	△
185457	LV.F-100-24-SST-M16x158-VD	100	M16	70	201	158	43	12.5	24	23	24	24	25000	391	△
185461	LV.F-100-24-SST-M20x98-VD	100	M20	70	141	98	43	12.5	24	23	24	24	25000	384	△
185463	LV.F-100-24-SST-M20x138-VD	100	M20	70	181	138	43	12.5	24	23	24	24	25000	464	△
185465	LV.F-100-24-SST-M20x158-VD	100	M20	70	201	158	43	12.5	24	23	24	24	25000	504	△
185467	LV.F-100-24-SST-M20x198-VD	100	M20	70	241	198	43	12.5	24	23	24	24	25000	589	△
185471	LV.F-100-24-SST-M24x98-VD	100	M24	70	141	98	43	12.5	24	23	24	24	25000	484	△
185473	LV.F-100-24-SST-M24x158-VD	100	M24	70	201	158	43	12.5	24	23	24	24	25000	659	△
185475	LV.F-100-24-SST-M24x198-VD	100	M24	70	241	198	43	12.5	24	23	24	24	25000	780	△
185501	LV.F-125-24-SST-M16x58-VD	125	M16	95	125	58	67	12.5	46	23	24	24	28000	399	△
185503	LV.F-125-24-SST-M16x98-VD	125	M16	95	165	98	67	12.5	46	23	24	24	28000	451	△
185505	LV.F-125-24-SST-M16x138-VD	125	M16	95	205	138	67	12.5	46	23	24	24	28000	502	△
185507	LV.F-125-24-SST-M16x158-VD	125	M16	95	225	158	67	12.5	46	23	24	24	28000	530	△
185511	LV.F-125-24-SST-M20x98-VD	125	M20	95	165	98	67	12.5	46	23	24	24	28000	523	△
185513	LV.F-125-24-SST-M20x138-VD	125	M20	95	205	138	67	12.5	46	23	24	24	28000	603	△
185515	LV.F-125-24-SST-M20x158-VD	125	M20	95	225	158	67	12.5	46	23	24	24	28000	643	△
185517	LV.F-125-24-SST-M20x198-VD	125	M20	95	265	198	67	12.5	46	23	24	24	28000	728	△
185521	LV.F-125-24-SST-M24x98-VD	125	M24	95	165	98	67	12.5	46	23	24	24	28000	623	△
185523	LV.F-125-24-SST-M24x158-VD	125	M24	95	225	158	67	12.5	46	23	24	24	28000	798	△
185525	LV.F-125-24-SST-M24x198-VD	125	M24	95	265	198	67	12.5	46	23	24	24	28000	919	△

PS. 備註

- 使用溫度：-30°C~100°C
- 透過兩個180°的盲孔用於地面安裝，使用工具敲穿塑膠隔膜(參見圖1)


訂貨： 交期： 天

185301

圖1

SP. 特長

- 由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21和EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易
- 無防滑墊底座即使在傾斜的表面上使用，底座下方的特殊壓花也能提供良好的穩定性和抓地力

**WA.** 注意

- 如果超過上表最大靜態荷重，可能會導致底座破裂
- 為防止運送途中碰傷，腳座(底座與螺栓)採用個別包裝，請客戶自行組立
- 螺帽需個別購買