



底座		螺栓
材質	顏色	材質
PA+玻纖	藍	SUS304

品號	描述	D	d	L	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
183101	LV.A-60-14-SST-M8x43-VD	60	M8	76	43	33	24	14	14	14000	63	△
183103	LV.A-60-14-SST-M8x68-VD	60	M8	101	68	33	24	14	14	14000	75	△
183111	LV.A-60-14-SST-M10x43-VD	60	M10	76	43	33	24	14	14	14000	72	△
183113	LV.A-60-14-SST-M10x68-VD	60	M10	101	68	33	24	14	14	14000	85	△
183115	LV.A-60-14-SST-M10x98-VD	60	M10	131	98	33	24	14	14	14000	99	△
183121	LV.A-60-14-SST-M12x43-VD	60	M12	76	43	33	24	14	14	14000	82	△
183123	LV.A-60-14-SST-M12x68-VD	60	M12	101	68	33	24	14	14	14000	100	△
183125	LV.A-60-14-SST-M12x98-VD	60	M12	131	98	33	24	14	14	14000	122	△
183131	LV.A-60-14-SST-M14x68-VD	60	M14	101	68	33	24	14	14	14000	123	△
183133	LV.A-60-14-SST-M14x98-VD	60	M14	131	98	33	24	14	14	14000	144	△
183135	LV.A-60-14-SST-M14x148-VD	60	M14	181	148	33	24	14	14	14000	227	△
183141	LV.A-60-14-SST-M16x68-VD	60	M16	101	68	33	24	16	14	14000	145	△
183143	LV.A-60-14-SST-M16x108-VD	60	M16	141	108	33	24	16	14	14000	199	△
183145	LV.A-60-14-SST-M16x148-VD	60	M16	181	148	33	24	16	14	14000	252	△
183147	LV.A-60-14-SST-M16x168-VD	60	M16	201	168	33	24	16	14	14000	279	△
183151	LV.A-60-24-SST-M16x58-VD	60	M16	101	58	43	24	24	24	18000	208	△
183153	LV.A-60-24-SST-M16x98-VD	60	M16	141	98	43	24	24	24	18000	260	△
183155	LV.A-60-24-SST-M16x138-VD	60	M16	181	138	43	24	24	24	18000	311	△
183157	LV.A-60-24-SST-M16x158-VD	60	M16	201	158	43	24	24	24	18000	339	△
183161	LV.A-60-24-SST-M20x98-VD	60	M20	141	98	43	24	24	24	18000	332	△
183163	LV.A-60-24-SST-M20x138-VD	60	M20	181	138	43	24	24	24	18000	412	△
183165	LV.A-60-24-SST-M20x158-VD	60	M20	201	158	43	24	24	24	18000	452	△
183167	LV.A-60-24-SST-M20x198-VD	60	M20	241	198	43	24	24	24	18000	537	△
183171	LV.A-60-24-SST-M24x98-VD	60	M24	141	98	43	24	24	24	18000	432	△
183173	LV.A-60-24-SST-M24x158-VD	60	M24	201	158	43	24	24	24	18000	607	△
183175	LV.A-60-24-SST-M24x198-VD	60	M24	241	198	43	24	24	24	18000	728	△
183201	LV.A-70-14-SST-M8x43-VD	70	M8	71	43	28	19	14	14	14000	61	△
183203	LV.A-70-14-SST-M8x68-VD	70	M8	96	68	28	19	14	14	14000	73	△
183211	LV.A-70-14-SST-M10x43-VD	70	M10	71	43	28	19	14	14	14000	70	△
183213	LV.A-70-14-SST-M10x68-VD	70	M10	96	68	28	19	14	14	14000	84	△
183215	LV.A-70-14-SST-M10x98-VD	70	M10	126	98	28	19	14	14	14000	97	△
183221	LV.A-70-14-SST-M12x43-VD	70	M12	71	43	28	19	14	14	14000	80	△
183223	LV.A-70-14-SST-M12x68-VD	70	M12	96	68	28	19	14	14	14000	98	△
183225	LV.A-70-14-SST-M12x98-VD	70	M12	126	98	28	19	14	14	14000	120	△
183231	LV.A-70-14-SST-M14x68-VD	70	M14	96	68	28	19	14	14	14000	121	△
183233	LV.A-70-14-SST-M14x98-VD	70	M14	126	98	28	19	14	14	14000	142	△
183235	LV.A-70-14-SST-M14x148-VD	70	M14	176	148	28	19	14	14	14000	225	△
183241	LV.A-70-14-SST-M16x68-VD	70	M16	96	68	28	19	16	14	14000	143	△
183243	LV.A-70-14-SST-M16x108-VD	70	M16	136	108	28	19	16	14	14000	197	△
183245	LV.A-70-14-SST-M16x148-VD	70	M16	176	148	28	19	16	14	14000	250	△
183247	LV.A-70-14-SST-M16x168-VD	70	M16	196	168	28	19	16	14	14000	277	△
183301	LV.A-80-14-SST-M8x43-VD	80	M8	76	43	33	24	14	14	16000	84	△
183303	LV.A-80-14-SST-M8x68-VD	80	M8	101	68	33	24	14	14	16000	96	△
183311	LV.A-80-14-SST-M10x43-VD	80	M10	76	43	33	24	14	14	16000	93	△
183313	LV.A-80-14-SST-M10x68-VD	80	M10	101	68	33	24	14	14	16000	106	△
183315	LV.A-80-14-SST-M10x98-VD	80	M10	131	98	33	24	14	14	16000	120	△
183321	LV.A-80-14-SST-M12x43-VD	80	M12	76	43	33	24	14	14	16000	103	△

品號	描述	D	d	L	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
183323	LV.A-80-14-SST-M12x68-VD	80	M12	101	68	33	24	14	14	16000	121	△
183325	LV.A-80-14-SST-M12x98-VD	80	M12	131	98	33	24	14	14	16000	143	△
183331	LV.A-80-14-SST-M14x68-VD	80	M14	101	68	33	24	14	14	16000	144	△
183333	LV.A-80-14-SST-M14x98-VD	80	M14	131	98	33	24	14	14	16000	165	△
183335	LV.A-80-14-SST-M14x148-VD	80	M14	181	148	33	24	14	14	16000	248	△
183341	LV.A-80-14-SST-M16x68-VD	80	M16	101	68	33	24	16	14	16000	166	△
183343	LV.A-80-14-SST-M16x108-VD	80	M16	141	108	33	24	16	14	16000	220	△
183345	LV.A-80-14-SST-M16x148-VD	80	M16	181	148	33	24	16	14	16000	273	△
183347	LV.A-80-14-SST-M16x168-VD	80	M16	201	168	33	24	16	14	16000	300	△
183351	LV.A-80-24-SST-M16x58-VD	80	M16	101	58	43	24	24	24	18000	228	△
183353	LV.A-80-24-SST-M16x98-VD	80	M16	141	98	43	24	24	24	18000	280	△
183355	LV.A-80-24-SST-M16x138-VD	80	M16	181	138	43	24	24	24	18000	331	△
183357	LV.A-80-24-SST-M16x158-VD	80	M16	201	158	43	24	24	24	18000	359	△
183361	LV.A-80-24-SST-M20x98-VD	80	M20	141	98	43	24	24	24	18000	352	△
183363	LV.A-80-24-SST-M20x138-VD	80	M20	181	138	43	24	24	24	18000	432	△
183365	LV.A-80-24-SST-M20x158-VD	80	M20	201	158	43	24	24	24	18000	472	△
183367	LV.A-80-24-SST-M20x198-VD	80	M20	241	198	43	24	24	24	18000	577	△
183371	LV.A-80-24-SST-M24x98-VD	80	M24	141	98	43	24	24	24	18000	452	△
183373	LV.A-80-24-SST-M24x158-VD	80	M24	201	158	43	24	24	24	18000	627	△
183375	LV.A-80-24-SST-M24x198-VD	80	M24	241	198	43	24	24	24	18000	748	△
183401	LV.A-100-14-SST-M8x43-VD	100	M8	76	43	33	24	14	14	18000	91	△
183403	LV.A-100-14-SST-M8x68-VD	100	M8	101	68	33	24	14	14	18000	103	△
183411	LV.A-100-14-SST-M10x43-VD	100	M10	76	43	33	24	14	14	18000	100	△
183413	LV.A-100-14-SST-M10x68-VD	100	M10	101	68	33	24	14	14	18000	112	△
183415	LV.A-100-14-SST-M10x98-VD	100	M10	131	98	33	24	14	14	18000	126	△
183421	LV.A-100-14-SST-M12x43-VD	100	M12	76	43	33	24	14	14	18000	110	△
183423	LV.A-100-14-SST-M12x68-VD	100	M12	101	68	33	24	14	14	18000	127	△
183425	LV.A-100-14-SST-M12x98-VD	100	M12	131	98	33	24	14	14	18000	148	△
183431	LV.A-100-14-SST-M14x68-VD	100	M14	101	68	33	24	14	14	18000	149	△
183433	LV.A-100-14-SST-M14x98-VD	100	M14	131	98	33	24	14	14	18000	170	△
183435	LV.A-100-14-SST-M14x148-VD	100	M14	181	148	33	24	14	14	18000	253	△
183441	LV.A-100-14-SST-M16x68-VD	100	M16	101	68	33	24	16	14	18000	171	△
183443	LV.A-100-14-SST-M16x108-VD	100	M16	141	108	33	24	16	14	18000	223	△
183445	LV.A-100-14-SST-M16x148-VD	100	M16	181	148	33	24	16	14	18000	275	△
183447	LV.A-100-14-SST-M16x168-VD	100	M16	201	168	33	24	16	14	18000	301	△
183451	LV.A-100-24-SST-M16x58-VD	100	M16	101	58	43	24	24	24	25000	254	△
183453	LV.A-100-24-SST-M16x98-VD	100	M16	141	98	43	24	24	24	25000	357	△
183455	LV.A-100-24-SST-M16x138-VD	100	M16	181	138	43	24	24	24	25000	357	△
183457	LV.A-100-24-SST-M16x158-VD	100	M16	201	158	43	24	24	24	25000	385	△
183461	LV.A-100-24-SST-M20x98-VD	100	M20	141	98	43	24	24	24	25000	378	△
183463	LV.A-100-24-SST-M20x138-VD	100	M20	181	138	43	24	24	24	25000	458	△
183465	LV.A-100-24-SST-M20x158-VD	100	M20	201	158	43	24	24	24	25000	498	△
183467	LV.A-100-24-SST-M20x198-VD	100	M20	241	198	43	24	24	24	25000	583	△
183471	LV.A-100-24-SST-M24x98-VD	100	M24	141	98	43	24	24	24	25000	478	△
183473	LV.A-100-24-SST-M24x158-VD	100	M24	201	158	43	24	24	24	25000	653	△
183475	LV.A-100-24-SST-M24x198-VD	100	M24	241	198	43	24	24	24	25000	774	△
183501	LV.A-125-24-SST-M16x58-VD	125	M16	125	58	67	46	24	24	28000	389	△
183503	LV.A-125-24-SST-M16x98-VD	125	M16	165	98	67	46	24	24	28000	441	△
183505	LV.A-125-24-SST-M16x138-VD	125	M16	205	138	67	46	24	24	28000	492	△
183507	LV.A-125-24-SST-M16x158-VD	125	M16	225	158	67	46	24	24	28000	520	△
183511	LV.A-125-24-SST-M20x98-VD	125	M20	165	98	67	46	24	24	28000	513	△
183513	LV.A-125-24-SST-M20x138-VD	125	M20	205	138	67	46	24	24	28000	633	△
183515	LV.A-125-24-SST-M20x158-VD	125	M20	225	158	67	46	24	24	28000	633	△
183517	LV.A-125-24-SST-M20x198-VD	125	M20	265	198	67	46	24	24	28000	718	△
183521	LV.A-125-24-SST-M24x98-VD	125	M24	165	98	67	46	24	24	28000	613	△
183523	LV.A-125-24-SST-M24x158-VD	125	M24	225	158	67	46	24	24	28000	788	△
183525	LV.A-125-24-SST-M24x198-VD	125	M24	265	198	67	46	24	24	28000	909	△

PS. 備註

・使用溫度：-30°C~100°C

訂貨： 交期：天

183101

SP. 特長

- ・由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21和EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易
- ・無防滑墊底座即使在傾斜的表面上使用，底座下方的特殊壓花也能提供良好的穩定性和抓地力

WA. 注意

- ・如果超過上表最大靜態荷重，可能會導致底座破裂
- ・為防止運送途中碰傷，腳座(底座與螺栓)採用個別包裝，請客戶自行組立
- ・螺帽需個別購買