



底座		螺栓
材質	顏色	材質
PA+玻纖	藍	SUS304

品號	描述	D	d	L	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
187101	LS.A-25-14-SST-M8x43-VD	25	M8	67	43	24	12	14	14	7000	33	△
187103	LS.A-25-14-SST-M8x68-VD	25	M8	92	68	24	12	14	14	7000	43	△
187111	LS.A-25-14-SST-M10x43-VD	25	M10	67	43	24	12	14	14	7000	43	△
187113	LS.A-25-14-SST-M10x68-VD	25	M10	92	68	24	12	14	14	7000	56	△
187115	LS.A-25-14-SST-M10x98-VD	25	M10	122	98	24	12	14	14	7000	70	△
187121	LS.A-25-14-SST-M12x43-VD	25	M12	67	43	24	12	14	14	7000	53	△
187123	LS.A-25-14-SST-M12x68-VD	25	M12	92	68	24	12	14	14	7000	71	△
187125	LS.A-25-14-SST-M12x98-VD	25	M12	122	98	24	12	14	14	7000	93	△
187131	LS.A-25-14-SST-M14x68-VD	25	M14	92	68	24	12	14	14	7000	86	△
187133	LS.A-25-14-SST-M14x98-VD	25	M14	122	98	24	12	14	14	7000	107	△
187135	LS.A-25-14-SST-M14x148-VD	25	M14	172	148	24	12	14	14	7000	190	△
187141	LS.A-25-14-SST-M16x68-VD	25	M16	92	68	24	12	16	14	7000	116	△
187143	LS.A-25-14-SST-M16x108-VD	25	M16	132	108	24	12	16	14	7000	167	△
187145	LS.A-25-14-SST-M16x148-VD	25	M16	172	148	24	12	16	14	7000	220	△
187147	LS.A-25-14-SST-M16x168-VD	25	M16	192	168	24	12	16	14	7000	247	△
187201	LS.A-32-14-SST-M8x43-VD	32	M8	68	43	25	15	14	14	9000	38	△
187203	LS.A-32-14-SST-M8x68-VD	32	M8	93	68	25	15	14	14	9000	48	△
187211	LS.A-32-14-SST-M10x43-VD	32	M10	68	43	25	15	14	14	9000	48	△
187213	LS.A-32-14-SST-M10x68-VD	32	M10	93	68	25	15	14	14	9000	61	△
187215	LS.A-32-14-SST-M10x98-VD	32	M10	123	98	25	15	14	14	9000	75	△
187221	LS.A-32-14-SST-M12x43-VD	32	M12	68	43	25	15	14	14	9000	58	△
187223	LS.A-32-14-SST-M12x68-VD	32	M12	93	68	25	15	14	14	9000	78	△
187225	LS.A-32-14-SST-M12x98-VD	32	M12	123	98	25	15	14	14	9000	98	△
187231	LS.A-32-14-SST-M14x68-VD	32	M14	93	68	25	15	14	14	9000	95	△
187233	LS.A-32-14-SST-M14x98-VD	32	M14	123	98	25	15	14	14	9000	116	△
187235	LS.A-32-14-SST-M14x148-VD	32	M14	173	148	25	15	14	14	9000	199	△
187241	LS.A-32-14-SST-M16x68-VD	32	M16	93	68	25	15	16	14	9000	121	△
187243	LS.A-32-14-SST-M16x108-VD	32	M16	133	108	25	15	16	14	9000	175	△
187245	LS.A-32-14-SST-M16x148-VD	32	M16	173	148	25	15	16	14	9000	228	△
187247	LS.A-32-14-SST-M16x168-VD	32	M16	193	168	25	15	16	14	9000	255	△
187301	LS.A-40-14-SST-M8x43-VD	40	M8	68	43	25	17	14	14	13000	42	△
187303	LS.A-40-14-SST-M8x68-VD	40	M8	93	68	25	17	14	14	13000	52	△
187311	LS.A-40-14-SST-M10x43-VD	40	M10	68	43	25	17	14	14	13000	52	△
187313	LS.A-40-14-SST-M10x68-VD	40	M10	93	68	25	17	14	14	13000	65	△
187315	LS.A-40-14-SST-M10x98-VD	40	M10	123	98	25	17	14	14	13000	79	△
187321	LS.A-40-14-SST-M12x43-VD	40	M12	68	43	25	17	14	14	13000	62	△
187323	LS.A-40-14-SST-M12x68-VD	40	M12	93	68	25	17	14	14	13000	80	△
187325	LS.A-40-14-SST-M12x98-VD	40	M12	123	98	25	17	14	14	13000	102	△
187331	LS.A-40-14-SST-M14x68-VD	40	M14	93	68	25	17	14	14	13000	95	△

品號	描述	D	d	L	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
187333	LS.A-40-14-SST-M14x98-VD	40	M14	123	98	25	17	14	14	13000	116	△
187335	LS.A-40-14-SST-M14x148-VD	40	M14	173	148	25	17	14	14	13000	199	△
187341	LS.A-40-14-SST-M16x68-VD	40	M16	93	68	25	17	16	14	13000	125	△
187343	LS.A-40-14-SST-M16x108-VD	40	M16	133	108	25	17	16	14	13000	179	△
187345	LS.A-40-14-SST-M16x148-VD	40	M16	173	148	25	17	16	14	13000	232	△
187347	LS.A-40-14-SST-M16x168-VD	40	M16	193	168	25	17	16	14	13000	259	△
187401	LS.A-50-14-SST-M8x43-VD	50	M8	70	43	27	19	14	14	13000	49	△
187403	LS.A-50-14-SST-M8x68-VD	50	M8	95	68	27	19	14	14	13000	59	△
187411	LS.A-50-14-SST-M10x43-VD	50	M10	70	43	27	19	14	14	13000	59	△
187413	LS.A-50-14-SST-M10x68-VD	50	M10	95	68	27	19	14	14	13000	72	△
187415	LS.A-50-14-SST-M10x98-VD	50	M10	125	98	27	19	14	14	13000	86	△
187421	LS.A-50-14-SST-M12x43-VD	50	M12	70	43	27	19	14	14	13000	69	△
187423	LS.A-50-14-SST-M12x68-VD	50	M12	95	68	27	19	14	14	13000	87	△
187425	LS.A-50-14-SST-M12x98-VD	50	M12	125	98	27	19	14	14	13000	109	△
187431	LS.A-50-14-SST-M14x68-VD	50	M14	95	68	27	19	14	14	13000	102	△
187433	LS.A-50-14-SST-M14x98-VD	50	M14	125	98	27	19	14	14	13000	123	△
187435	LS.A-50-14-SST-M14x148-VD	50	M14	175	148	27	19	14	14	13000	206	△
187441	LS.A-50-14-SST-M16x68-VD	50	M16	95	68	27	19	16	14	13000	132	△
187443	LS.A-50-14-SST-M16x108-VD	50	M16	135	108	27	19	16	14	13000	185	△
187445	LS.A-50-14-SST-M16x148-VD	50	M16	175	148	27	19	16	14	13000	239	△
187447	LS.A-50-14-SST-M16x168-VD	50	M16	195	168	27	19	16	14	13000	266	△
187501	LS.A-60-14-SST-M8x43-VD	60	M8	76	43	33	24	14	14	14000	64	△
187503	LS.A-60-14-SST-M8x68-VD	60	M8	101	68	33	24	14	14	14000	76	△
187511	LS.A-60-14-SST-M10x43-VD	60	M10	76	43	33	24	14	14	14000	73	△
187513	LS.A-60-14-SST-M10x68-VD	60	M10	101	68	33	24	14	14	14000	86	△
187515	LS.A-60-14-SST-M10x98-VD	60	M10	131	98	33	24	14	14	14000	100	△
187521	LS.A-60-14-SST-M12x43-VD	60	M12	76	43	33	24	14	14	14000	83	△
187523	LS.A-60-14-SST-M12x68-VD	60	M12	101	68	33	24	14	14	14000	101	△
187525	LS.A-60-14-SST-M12x98-VD	60	M12	131	98	33	24	14	14	14000	123	△
187531	LS.A-60-14-SST-M14x68-VD	60	M14	101	68	33	24	14	14	14000	124	△
187533	LS.A-60-14-SST-M14x98-VD	60	M14	131	98	33	24	14	14	14000	145	△
187535	LS.A-60-14-SST-M14x148-VD	60	M14	181	148	33	24	14	14	14000	228	△
187541	LS.A-60-14-SST-M16x68-VD	60	M16	101	68	33	24	16	14	14000	146	△
187543	LS.A-60-14-SST-M16x108-VD	60	M16	141	108	33	24	16	14	14000	200	△
187545	LS.A-60-14-SST-M16x148-VD	60	M16	181	148	33	24	16	14	14000	253	△
187547	LS.A-60-14-SST-M16x168-VD	60	M16	201	168	33	24	16	14	14000	280	△
187551	LS.A-60-24-SST-M16x58-VD	60	M16	101	58	43	24	24	24	18000	209	△
187553	LS.A-60-24-SST-M16x98-VD	60	M16	141	98	43	24	24	24	18000	262	△
187555	LS.A-60-24-SST-M16x138-VD	60	M16	181	138	43	24	24	24	18000	313	△
187557	LS.A-60-24-SST-M16x158-VD	60	M16	201	158	43	24	24	24	18000	341	△
187561	LS.A-60-24-SST-M20x98-VD	60	M20	141	98	43	24	24	24	18000	334	△
187563	LS.A-60-24-SST-M20x138-VD	60	M20	181	138	43	24	24	24	18000	415	△
187565	LS.A-60-24-SST-M20x158-VD	60	M20	201	158	43	24	24	24	18000	455	△
187567	LS.A-60-24-SST-M20x198-VD	60	M20	241	198	43	24	24	24	18000	541	△
187571	LS.A-60-24-SST-M24x98-VD	60	M24	141	98	43	24	24	24	18000	435	△
187573	LS.A-60-24-SST-M24x158-VD	60	M24	201	158	43	24	24	24	18000	612	△
187575	LS.A-60-24-SST-M24x198-VD	60	M24	241	198	43	24	24	24	18000	734	△

PS. 備註

・使用溫度：-30°C~100°C

訂貨： 交期： 天

187101

SP. 特長

・由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21 和 EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易

WA. 注意

- ・如果超過上表最大靜態荷重，可能會導致底座破裂
- ・為防止運送途中碰傷，腳座(底座與螺栓)採用個別包裝，請客戶自行組立
- ・螺帽需個別購買