



<sup>2)</sup> 厚度 < 1 mm : 導角 = 20°

倒角和 d1 的關係

d1 [mm]:	Ø 1-6	Ø 6-12	Ø 12-30	Ø > 30
f [mm]:	0.3	0.5	0.8	1.2

尺寸 [mm]

d1	d1-公差 <sup>3)</sup>	d2	b1 h13	產品型號
3.0	+0.010 +0.058	4.5	3.0	X6SM-0304-03
5.0	+0.010 +0.058	7.0	5.0	X6SM-0507-05
6.0	+0.010 +0.058	8.0	6.0	X6SM-0608-06
8.0	+0.013 +0.071	10.0	10.0	X6SM-0810-10
10.0	+0.013 +0.071	12.0	10.0	X6SM-1012-10
12.0	+0.016 +0.086	14.0	12.0	X6SM-1214-12
16.0	+0.016 +0.086	18.0	15.0	X6SM-1618-15
20.0	+0.020 +0.104	23.0	20.0	X6SM-2023-20
25.0	+0.020 +0.104	28.0	30.0	X6SM-2528-30
30.0	+0.020 +0.104	34.0	30.0	X6SM-3034-30
35.0	+0.025 +0.125	39.0	40.0	X6SM-3539-40
40.0	+0.025 +0.125	44.0	40.0	X6SM-4044-40
50.0	+0.025 +0.125	55.0	40.0	X6SM-5055-40

<sup>3)</sup> 按壓組裝後 測試方法 ▶ 頁碼 57

## 產品型號

類型 尺寸 [mm]

**X6 S M-0304-03**

iglidur® 材質	型號 S	公制	內徑 - Ø d1	外徑 - Ø d2	長度 b1
-------------	------	----	-----------	-----------	-------

**i** 尺寸符合 ISO 3547-1 標準  
且提供特殊尺寸