



<sup>2)</sup> 厚度 < 1 mm : 導角 = 20°

倒角和 d1 的關係

|          |       |        |         |        |
|----------|-------|--------|---------|--------|
| d1 [mm]: | Ø 1-6 | Ø 6-12 | Ø 12-30 | Ø > 30 |
| f [mm]:  | 0.3   | 0.5    | 0.8     | 1.2    |

尺寸 [mm]

| d1   | d1-<br>公差 <sup>3)</sup> | d2   | b1<br>h13 | 零件號         |
|------|-------------------------|------|-----------|-------------|
| 3.0  | +0.006<br>+0.046        | 4.5  | 3.0       | HSM-0304-03 |
| 4.0  |                         | 5.5  | 4.0       | HSM-0405-04 |
| 5.0  | +0.010                  | 7.0  | 5.0       | HSM-0507-05 |
| 6.0  | +0.058                  | 8.0  | 3.0       | HSM-0608-03 |
| 6.0  |                         | 8.0  | 6.0       | HSM-0608-06 |
| 8.0  |                         | 10.0 | 8.0       | HSM-0810-08 |
| 8.0  | +0.013                  | 10.0 | 10.0      | HSM-0810-10 |
| 10.0 | +0.071                  | 12.0 | 6.0       | HSM-1012-06 |
| 10.0 |                         | 12.0 | 10.0      | HSM-1012-10 |
| 12.0 |                         | 14.0 | 10.0      | HSM-1214-10 |
| 12.0 |                         | 14.0 | 12.0      | HSM-1214-12 |
| 12.0 |                         | 14.0 | 15.0      | HSM-1214-15 |
| 12.0 |                         | 14.0 | 20.0      | HSM-1214-20 |
| 14.0 | +0.016                  | 16.0 | 20.0      | HSM-1416-20 |
| 15.0 | +0.086                  | 17.0 | 15.0      | HSM-1517-15 |
| 16.0 |                         | 18.0 | 15.0      | HSM-1618-15 |
| 16.0 |                         | 18.0 | 20.0      | HSM-1618-20 |
| 16.0 |                         | 18.0 | 25.0      | HSM-1618-25 |

<sup>3)</sup> 按壓組裝後 測試方法 ▶ 頁碼 57

## 產品型號

類型 尺寸 [mm]

H S M-0304-03

|             |      |    |           |           |       |
|-------------|------|----|-----------|-----------|-------|
| iglidur® 材質 | 型號 S | 公制 | 內徑 - Ø d1 | 外徑 - Ø d2 | 長度 b1 |
|-------------|------|----|-----------|-----------|-------|

**i** 尺寸符合 ISO 3547-1 標準  
且提供特殊尺寸

| d1   | d1-<br>公差 <sup>3)</sup> | d2   | b1<br>h13 | 零件號         |
|------|-------------------------|------|-----------|-------------|
| 18.0 | +0.016                  | 20.0 | 15.0      | HSM-1820-15 |
| 18.0 | +0.086                  | 20.0 | 25.0      | HSM-1820-25 |
| 20.0 |                         | 23.0 | 20.0      | HSM-2023-20 |
| 20.0 |                         | 23.0 | 30.0      | HSM-2023-30 |
| 22.0 |                         | 25.0 | 20.0      | HSM-2225-20 |
| 25.0 | +0.020                  | 28.0 | 15.0      | HSM-2528-15 |
| 25.0 | +0.104                  | 28.0 | 20.0      | HSM-2528-20 |
| 30.0 |                         | 34.0 | 20.0      | HSM-3034-20 |
| 30.0 |                         | 34.0 | 30.0      | HSM-3034-30 |
| 30.0 |                         | 34.0 | 40.0      | HSM-3034-40 |
| 32.0 |                         | 36.0 | 30.0      | HSM-3236-30 |
| 35.0 |                         | 39.0 | 40.0      | HSM-3539-40 |
| 40.0 | +0.025                  | 44.0 | 20.0      | HSM-4044-20 |
| 40.0 | +0.125                  | 44.0 | 50.0      | HSM-4044-50 |
| 45.0 |                         | 50.0 | 30.0      | HSM-4550-30 |
| 50.0 |                         | 55.0 | 40.0      | HSM-5055-40 |
| 55.0 | +0.030                  | 60.0 | 26.0      | HSM-5560-26 |
| 60.0 | +0.150                  | 65.0 | 60.0      | HSM-6065-60 |
| 70.0 |                         | 75.0 | 50.0      | HSM-7075-50 |