



²⁾ 厚度 < 1 mm : 導角 = 20°

倒角和 d1 的關係

d1 [mm]:	Ø 1-6	Ø 6-12	Ø 12-30	Ø > 30
f [mm]:	0.3	0.5	0.8	1.2

尺寸 [mm]

d1	d1-公差 ³⁾	d2	b1 h13	產品型號
6.0	+0.020	8.0	10.0	QSM-0608-10
	+0.068			
8.0	+0.025	10.0	8.0	QSM-0810-08
10.0	+0.083	12.0	10.0	QSM-1012-10
12.0		14.0	10.0	QSM-1214-10
12.0		14.0	20.0	QSM-1214-20
16.0	+0.032	18.0	8.0	QSM-1618-08
16.0	+0.102	18.0	12.5	QSM-1618-12
16.0		18.0	20.0	QSM-1618-20
18.0		20.0	20.0	QSM-1820-20
20.0		22.0	15.0	QSM-2022-15
20.0		23.0	15.0	QSM-2023-15
20.0		23.0	20.0	QSM-2023-20
20.0		23.0	25.0	QSM-2023-25
20.0	+0.040	23.0	30.0	QSM-2023-30
25.0	+0.124	28.0	25.0	QSM-2528-25
25.0		28.0	48.0	QSM-2528-48
30.0		34.0	20.0	QSM-3034-20
30.0		34.0	35.0	QSM-3034-35
30.0		34.0	40.0	QSM-3034-40
35.0	+0.050	39.0	15.0	QSM-3539-15
	+0.150			

³⁾ 按壓組裝後。測試方法 ▶ 頁碼 57

產品型號

類型 尺寸 [mm]

Q S M_0608_10

iglidur® 材質	型號 S	公制	內徑 - Ø d1	外徑 - Ø d2	長度 b1
-------------	------	----	-----------	-----------	-------

i 尺寸符合 ISO 3547-1 標準
且提供特殊尺寸

inch 也可選用英制尺寸
▶ 見頁碼 1417

d1	d1-公差 ³⁾	d2	b1 h13	產品型號
35.0		39.0	30.0	QSM-3539-30
35.0		39.0	35.0	QSM-3539-35
35.0		39.0	50.0	QSM-3539-50
40.0		44.0	30.0	QSM-4044-30
40.0		44.0	40.0	QSM-4044-40
40.0	+0.050	44.0	47.0	QSM-4044-47
45.0	+0.150	50.0	25.2	QSM-4550-252
45.0		50.0	50.0	QSM-4550-50
50.0		55.0	50.0	QSM-5055-50
50.0		55.0	60.0	QSM-5055-60
50.0		55.0	80.0	QSM-5055-80
55.0		60.0	50.0	QSM-5560-50
60.0		65.0	50.0	QSM-6065-50
65.0	+0.060	70.0	34.0	QSM-6570-34
70.0	+0.180	75.0	50.0	QSM-7075-50
75.0		80.0	40.0	QSM-7580-40
80.0		85.0	60.0	QSM-8085-60
90.0	+0.072	95.0	50.0	QSM-9095-50
	+0.212			