

drylin® R 壓配軸承 | 產品範圍

由 iglidur® L100 材質製成

02439



訂購

類型

尺寸

W L M-0608-10

igidur® L100	L1 系列	公制	內徑 Ø	外徑 Ø	長度
--------------	-------	----	------	------	----



- 極耐磨耗
- 低摩擦係數



⁸⁰⁾ 用塞規測量

請注意: 安裝說明 ▶ 頁碼 981

材質表 ▶ 頁碼 1495



最低溫度 -40 ° C

耐高溫達 +100 ° C

尺寸 [mm]

d1	d1-公差 ⁸⁰⁾	d2	b1	bs	產品型號
6	+0.000 +0.040	8	10	6	WLM-0608-10
8	+0.000 +0.050	10	12	8	WLM-0810-12
10	+0.000 +0.050	12	14.5	10	WLM-1012-14
10	+0.000 +0.050	12	16	10	WLM-1012-16
12	+0.000 +0.050	14	16	10	WLM-1214-16
12	+0.000 +0.050	14	25	15	WLM-1214-25
16	+0.000 +0.050	18	18	10	WLM-1618-18
16	+0.000 +0.050	18	26	16	WLM-1618-26
20	+0.000 +0.060	23	22.5	12.5	WLM-2023-22
20	+0.000 +0.060	23	30	20	WLM-2023-30
22	+0.000 +0.060	25	30	20	WLM-2225-30
25	+0.000 +0.060	28	29	19	WLM-2528-29
25	+0.000 +0.060	28	35	25	WLM-2528-35
30	+0.000 +0.060	34	34	24	WLM-3034-34
30	+0.000 +0.060	34	40	30	WLM-3034-40
40	+0.000 +0.060	44	40	30	WLM-4044-40
40	+0.000 +0.060	44	50	40	WLM-4044-50
50	+0.000 +0.070	55	50	40	WLM-5055-50
50	+0.000 +0.070	55	60	50	WLM-5055-60