


RoHS

SQH
二通接管




品號	管徑		C1	C2	d	F	G	L	有效斷面積 mm ²	質量 (g)
	D1	D2								
SQH4	4	4	14.9	14.9	3.3	15.9	10.4	31.7	4.2	4
SQH6-4	6	4	17.1	15.5	3.2	17.8	12.3	35.8		6
SQH6	6	6	17.1	17.1		3.3	18.1	12.4	36.1	10
SQH8-6	8	6	18.6	17.1	21		14.3	41.9		
SQH8	8	8	18.6	18.6	4.2	20.9	14.3	41.8	16	16
SQH10-8	10	8	20.9	18.6		22.9	17.7	46.7		
SQH10	10	10	20.9	20.9	4.2	23.8	17.8	47.5	30	22
SQH12-10	12	10	23.7	20.9		26.2	21.2	52.7		
SQH12	12	12	23.7	23.7	26.5	21.2	52.9			

Sp. 特長

· 適用於二通同向同尺寸及不同尺寸的配管

SQV
L型二通接管




品號	管徑		C1	C2	d	F	G	L	有效斷面積 mm ²	質量 (g)
	D1	D2								
SQV4-4	4	4	14.5	14.5	3.3	7.2	10.5	22.5	4.2	8
SQV6-6	6	6	16.6	16.6		8	12.4	26.4	12.6	10
SQV8-8	8	8	17.6	17.6	4.2	10	14.3	29.4	19.6	12
SQV10-10	10	10	19.4	19.4		10.9	17.8	34	33.2	18
SQV12-12	12	12	22.7	22.7	12.6	21.2	40.1	50.3	28	

Sp. 特長

· 適用於固定90°角彎管處使用

SQE
T型三通接管



品號	管徑		C1	C2	d	E1	E2	G	有效斷面積 mm ²	質量 (g)
	D1	D2								
SQE4	4	4	14.6	14.6	3.2	17.5	17.5	10.5	3.5	6.5
SQE6-4	6	4	17	15.6		20.6	20.6	12.4	4.2	8.2
SQE6	6	6	17	17	3.3	23.6	23.4	14.3	10	9
SQE8-6	8	6	18.8	17.5						
SQE8	8	8	18.8	18.8	4.2	26.1	26.1	17.8	16	22
SQE10-8	10	8	20.2	18.8						
SQE10	10	10	20.2	20.2	4.2	30.1	30	21.2	30	36
SQE12-10	12	10	22.8	20.2						
SQE12	12	12	22.8	22.8	30.1	30.1				

Sp. 特長

· T型90°同尺寸及不同尺寸的配管

Ps. 備註

- 使用注意事項請參閱調速閥、接頭組件之使用注意事項
- 起訂量為10pcs/包

訂貨： 交期： 天

SQH4