


(RoHS)

SQLS
加長L型接頭

SP. 特長

· 適用於高尺寸直角90°方向的配管場合




品號	管徑 D	牙徑	A	B	C	E	G	L	對邊 H	有效斷面積 mm ²	質量 g
SQLS4-01	4	1/8"	5.5	32.9	14.7	17.6	10.5	18.7	10	4.2	20
SQLS4-02		1/4"	9	33.8				21.7	14		36
SQLS6-01	6	1/8"	5.5	35.8	17.1	20.7	12.5	18.5	10	10	20
SQLS6-02		1/4"	8	37				21.3	14		32
SQLS8-01	8	1/8"	5.5	43.4	18.7	23	14.3	22.3	12	16	42.5
SQLS8-02		1/4"	8	44.6				24.9	14		43.5
SQLS8-03		3/8"						25.9	17		54
SQLS10-02	10	1/4"	53.4	20.9	26.6	17.8	27.4	17	30	62.5	
SQLS10-03		3/8"	52.8				27.6			55.5	
SQLS12-03	12	3/8"	9	62.8	23.6	30.5	21.1	30.4	17	50	70
SQLS12-04		1/2"	10	62.6				33.9	21		96

MSQJ
45°接頭



SP. 特長

· 適用於斜角45°方向的配管場合




品號	管徑 D	牙徑 M	A	B	C	G	L	對邊 H	有效斷面積 mm ²	質量 g
MSQJ4-M3	4	M30.5	3	12.3	10.6	9	25.6	1.5	2	3
MSQJ4-M5		M5×0.8	3.5	12.9			26.2	2.5	5.4	
MSQJ4-01		PT1/8"	6	16.8			30	3	7.8	
MSQJ6-M5	6	M5×0.8	3.5	15.7	12	11	31.3	2.5	5.4	8
MSQJ6-01		PT1/8"	6	16.4			32	4	13.8	

SQLJ
L型插管式接頭

SP. 特長

· 適用於直立接頭轉90°固定配管時使用



品號	管徑		B	C1	C2	E	G	L	有效斷面積 mm ²	質量 g
	D1	D2								
SQLJ4-4	4	4	25.8	14.5	15.3	17.5	10.5	15.5	2	2.5
SQLJ6-4		6				17.2			19.8	12.4
SQLJ6-6	6	6	28.8	16.5	17.2	19.6	14.3	21.6	7.5	4
SQLJ8-6						8			22.6	10.4
SQLJ8-8	8	8	32.1	18.5	18.2	23.1	14.3	21.6	16.5	5.5
SQLJ10-8						10			17.8	17.4
SQLJ10-10	10	10	33.8	19.2	20.4	24.2	17.8	22.6	30	13
SQLJ12-10						12			19.7	28
SQLJ12-12	12	12	40.3	21.9	24.7	28.3	21.2	26.3	42.5	14.5

PS. 備註

- 使用注意事項…P.1185
- 起訂量為10pcs/包

訂貨： 交期：天

SQLS4-01