


高荷重脚轮

GXT series

 500~600kg

 RoHS









 -10~90°C



产品说明: 锻造脚轮座, 使用2列推力球轴承优化旋高荷重转性的结构, 坚固的焊接支架, 手动刹车系统, 使用特殊形态的轮轴强化旋转性,

表面处理: 粉末喷涂, 镀锌

* 4轮允许承载 = 单轮运行承载 × 3

万向型	万向刹车型	轮子种类	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
GXT-80-ASS	GXT-80-BSS	HUD	80	48	500	120	40	TM32-4 or M36x4.0P	115+15	20
GXT-100-ASS	GXT-100-BSS		100	48	600	140	40			
GXT-80-ASS	GXT-80-BSS	MCD	80	48	500	120	40	TM32-4 or M36x4.0P	115+15	20
GXT-100-ASS	GXT-100-BSS		100	48	600	140	40			
GXT-100-ASS	GXT-100-BSS	NYD	100	48	600	140	40	TM32-4 or M36x4.0P	115+15	20

选项

						
产品编号	HUD	MCD	NYD			
产品特征	浇注型聚氨酯(D70)	MC尼龙(D80)	尼龙66(D70)			
适用型号	80 ~ 100	80 ~ 100	100			