


(RoHS)

SQX
四通接管




Sp. 特長

· 四通各90°同尺寸及不同尺寸的配管

品號	管徑		C1	C2	d	E1	E2	F	G	有效斷面積 mm ²	質量 (g)
	D1	D2									
SQX4	4	4	14.6	14.6	3.2	17.4	17.4	7.3	10.5	4.2	8.5
SQX6-4	6	4	17.1	17.1		20.7	20.7	8.1	12.4		11.5
SQX6	6	6	17.1	17.6	3.2	23.6	23.4	9.2	14.3	10	18
SQX8-6	8	6	18.9	18.9							23.6
SQX8	8	8	18.9	18.9	4.2	26	26	11.3	17.8	16	32
SQX10-8	10	8	20.3	20.3							26
SQX10	10	10	20.3	20.3	4.2	29.7	29.7	13.0	21.3	30	47
SQX12-10	12	10	28.2	28.2							29.7
SQX12	12	12	28.2	28.2						50	45

SQF
五通接管




Sp. 特長

· 五通垂直90°同尺寸及不同尺寸的配管

品號	管徑		C1	C2	d	E	F1	F2	L	G	J	有效斷面積 mm ²	質量 (g)
	D1	D2											
SQF4	4	4	14.6	14.6	3.2	20.6	8.1	40.6	65.4	12.4	12.4	4.2	16
SQF6-4	6	4	17.1	17.1		20.7							
SQF6	6	6	17.1	17.1	3.2	25.8	11.3	47	76.4	14.3	14.3	10	16.5
SQF8-6	8	6	18.9	18.9									26
SQF8	8	8	18.9	18.9	4.2	26.4	10.8	57.1	86.7	17.8	17.8	16	22
SQF10-8	10	8	20.2	20.2									26.4
SQF10	10	10	20.2	20.2								30	39

SQHJ
插管式接頭



Sp. 特長

· 適用於接頭配管延長時使用

品號	管徑		B	C1	C2	G	L	有效斷面積 mm ²	質量 (g)
	D1	D2							
SQHJ6-4	6	4	41.5	17	14.4	10.5	24.5	5.3	3
SQHJ8-4	8	4	45	18					12.4
SQHJ8-6	8	6	46.8	20	16.5	14.3	26.8	9.0	4.5
SQHJ10-6	10	6	47	20					17.8
SQHJ10-8	10	8	47	20	17.8	17.8	30.5	20	7
SQHJ12-8	12	8	54	23.5					19.2
SQHJ12-10	12	10	54	23.5				35	8

Ps. 備註

- 使用注意事項請參閱調速閥、接頭組件之使用注意事項
- 起訂量為10pcs/包

訂貨： 交期： 天

SQX4