



本體		螺帽		入子	
材質	處理	材質	處理	材質	處理
鋼	鍍鋅	鋼	鍍鎳	鋼	鍍鎳

品號	d1 (D2h9)	d2 (D1H9)	l1	l2	l3	WS	T _A max. N _m	M max. N _m	F _a max. KN	P _w max. N/mm ²	P _N max. N/mm ²	質量 (g)	庫存	備註
25050.0105	5	12	19	15	9	14	9.9	10.1	4	264	119	18	•	
25050.0106	6						12.1	220		17				
25050.0108	8	14	22	17	11	16	16.9	23.4	5.8	179	121	23	•	
25050.0109	9	18	24	19	12	22	34.9	43.7	9.7	245	127	47	•	
25050.0110	10						48.6	221		46				
25050.0111	11	20	24	19	12	22	43.8	59.9	10.9	225	128	47	•	
25050.0112	12						65.3	206		45				
25050.0114	14	24	28	22	15	27	65	93	13.3	178	107	78	•	
25050.0115	15						99	166		75				
25050.0116	16							106		156		70		
25050.0118	18	30	36	27	17	36	161	223	24.8	224	145	179	•	
25050.0119	19						235	212		169				
25050.0120	20							248		201		213		
25050.0122	22	38	41	30	20	46	250	349	31.8	197	122	341	•	
25050.0124	24						381	180		320				
25050.0125	25							397		173		310		
25050.0128	28	42	44	33	23	50	355	565	40.4	174	123	370	•	
25050.0130	30						605	162		348				
25050.0132	32	50	51	38	28	55	490	764	47.8	166	112	555	•	
25050.0135	35						836	151		501				
25050.0814	-	-	-	-	-	14	-	-	-	-	-	45	•	專用 把手
25050.0816	-	-	-	-	-	16	-	-	-	-	-	51	•	
25050.0822	-	-	-	-	-	22	-	-	-	-	-	115	•	
25050.0827	-	-	-	-	-	27	-	-	-	-	-	315	•	
25050.0836	-	-	-	-	-	36	-	-	-	-	-	706	•	
25050.0846	-	-	-	-	-	46	-	-	-	-	-	612	•	
25050.0850	-	-	-	-	-	50	-	-	-	-	-	870	•	
25050.0855	-	-	-	-	-	55	-	-	-	-	-	1125	•	

SP 特長

- ・ 旋轉螺帽即可鎖固
- ・ 適用於鏈輪、齒輪、皮帶輪、凸輪把手…等之鎖固

EX 使用例

訂貨： 交期：

25050.0105

PS 備註

- ・ T_A = 鎖緊力矩
- ・ M = 可轉移力矩
- ・ F_a = 可轉移驅動力矩
- ・ P_w = 軸面壓力
- ・ P_N = 鞍面壓力

