



3 Type

- A** With 2 key rings
- B** With mounting tab and key ring
- C** With 2 mounting tabs

1 2

Length l	d ₁	d ₂	Static load in N ≈		Type A and type B are ideal suitable for ball lock pins and locking pins with axial lock
			With key ring	Without key ring	
150	14 *	1	75	1500	* - GN 113.11, GN 113.12 for pin Ø 5, Ø 6 - GN 113.1, GN 113.3, GN 113.4, GN 113.7, GN 113.8, GN 113.9, GN 113.10, GN 113.30, GN 214.2, GN 214.3, GN 214.6 for pin Ø 5, Ø 6, Ø 8 - GN 113.5, GN 113.6, GN 114.2, GN 114.3, GN 114.6, GN 124.1, GN 124.2 for all pins diameters ** - GN 113.11, GN 113.12, GN 314 for pin Ø 8, Ø 10, Ø 12 - GN 113.1, GN 113.3, GN 113.4, GN 113.7, GN 113.8, GN 113.9, GN 113.10, GN 113.30, GN 214.2, GN 214.3, GN 214.6 for pin Ø 10, Ø 12, Ø 16, Ø 20, Ø 25 *** - GN 113.11, GN 113.12, GN 314 for pin Ø 16, Ø 20, Ø 25
150	18 **	1,3	125	1500	
150	24 ***	1,5	140	1500	
200	14 *	1	75	1500	
200	18 **	1,3	125	1500	
200	24 ***	1,5	140	1500	
320	14 *	1	75	1500	
320	18 **	1,3	125	1500	
320	24 ***	1,5	140	1500	

Specification

- Retaining cable
Stainless steel AISI 316
Plastic coated (PVC)
Transparent TR
- Mounting tab
Stainless steel AISI 316
Plain
- Key ring
Stainless steel AISI 316 Ti
Plain, tumbled
- Press sleeves
Stainless steel AISI 316
- *Stainless Steel Characteristics* → Page QVX
- RoHS

4

Information

Retaining cables GN 111.8 are available in 3 different types and can therefore be used in a wide range of applications, e.g. for loss protection or as connecting and mounting cables.

Due to the selection of materials, the retaining cables are suitable for use in highly corrosive environments.

On delivery the key rings are already mounted on the retaining cable. With type A, both rings have the same diameter d₁.

For all types the loops are reversed laterally and attached parallel to each other, which is not entirely considered in the simplified drawing. The load values given in the table are non-binding guide values and rule out any liability.

How to order (Type C)

GN 111.8-150-C-TR

1	Length l
3	Type
4	Color

How to order (Type A and B)

GN 111.8-200-18-A-TR

1	Length l
2	d ₁
3	Type
4	Color

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9

