




圖 6



外輪	POM
軸承	鋼

品號	備註	D 0 -0.1	W 0 -0.2	C ±0.4	L ±0.5	N	荷重 (N)	庫存	
K-DR-19-B0.5	圖6	19	6	0.5	8	8.2	49	·	
K-DR-19-B1-14				1	14				
K-DR-19-B1.5				1.5	8				
K-DR-19-B3.5				3.5					
K-DR-22-B0.5-4.5		22		7	0.5	4.5	9.5	196	·
K-DR-22-B0.5					8				
K-DR-22-B1-10					1	10			
K-DR-22-B3-10.5					3	10.5			
K-DR-22-B3.6-12.4					3.6	12.4			
K-DR-22-B3.6-14.5						14.5			
K-DR-24-B0.5		24		7	0.5	8	9.5	196	·
K-DR-24-B3-10.5					3	10.5			
K-DR-26-B0.5-4.5		26		7	0.5	4.5	9.5	196	·
K-DR-26-B0.5					8				
K-DR-26-B3-10.5					3	10.5			
K-DR-26-B3.6-12.4					3.6	12.4			
K-DR-26-B5-11					5	11			
K-DR-28-B0.5		28		7	0.5	8	9.5	196	·
K-DR-28-B2-15					2	15			
K-DR-28-B3-10.5					3	10.5			
K-DR-30-B0.5	30		7	0.5	8	9.5	196	·	
K-DR-30-B3-10.5				3	10.5				
K-DR-30-B3.6-12.4				3.6	12.4				

Ps. 備註

- 溫度範圍：0°C~40°C
- 滾輪請勿施予軸向荷重
- 容許荷重是本公司300RPM/100萬回的測試值
- 1N=0.101972kgf

訂貨： 交期： 天 庫存
K-DR-19-B0.5 其它

Wa. 注意

- 非庫存品必須以101pcs為單位購買之