



底座		螺栓		防滑墊	
材質	顏色	材質	材質	硬度	
PA+玻纖	藍	SUS304	NBR	蕭氏A70	

品號	描述	D	d	d1	L	L1	l	l1	d2	h	h1	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
186301	LV.F-80-14-AS-SST-M8x43-VD	80	M8	54	76	79	43	33	8.5	24	23	14	14	16000	112	△
186303	LV.F-80-14-AS-SST-M8x68-VD	80	M8	54	101	104	68	33	8.5	24	23	14	14	16000	124	△
186311	LV.F-80-14-AS-SST-M10x43-VD	80	M10	54	76	79	43	33	8.5	24	23	14	14	16000	121	△
186313	LV.F-80-14-AS-SST-M10x68-VD	80	M10	54	101	104	68	33	8.5	24	23	14	14	16000	134	△
186315	LV.F-80-14-AS-SST-M10x98-VD	80	M10	54	131	134	98	33	8.5	24	23	14	14	16000	148	△
186321	LV.F-80-14-AS-SST-M12x43-VD	80	M12	54	76	79	43	33	8.5	24	23	14	14	16000	131	△
186323	LV.F-80-14-AS-SST-M12x68-VD	80	M12	54	101	104	68	33	8.5	24	23	14	14	16000	149	△
186325	LV.F-80-14-AS-SST-M12x98-VD	80	M12	54	131	134	98	33	8.5	24	23	14	14	16000	171	△
186331	LV.F-80-14-AS-SST-M14x68-VD	80	M14	54	101	104	68	33	8.5	24	23	14	14	16000	172	△
186333	LV.F-80-14-AS-SST-M14x98-VD	80	M14	54	131	134	98	33	8.5	24	23	14	14	16000	193	△
186335	LV.F-80-14-AS-SST-M14x148-VD	80	M14	54	181	184	148	33	8.5	24	23	14	14	16000	276	△
186341	LV.F-80-14-AS-SST-M16x68-VD	80	M16	54	101	104	68	33	8.5	24	23	16	14	16000	194	△
186343	LV.F-80-14-AS-SST-M16x108-VD	80	M16	54	141	144	108	33	8.5	24	23	16	14	16000	248	△
186345	LV.F-80-14-AS-SST-M16x148-VD	80	M16	54	181	184	148	33	8.5	24	23	16	14	16000	301	△
186347	LV.F-80-14-AS-SST-M16x168-VD	80	M16	54	201	204	168	33	8.5	24	23	16	14	16000	328	△
186351	LV.F-80-24-AS-SST-M16x58-VD	80	M16	54	101	104	58	43	8.5	24	23	24	24	18000	256	△
186353	LV.F-80-24-AS-SST-M16x98-VD	80	M16	54	141	144	98	43	8.5	24	23	24	24	18000	308	△
186355	LV.F-80-24-AS-SST-M16x138-VD	80	M16	54	181	184	138	43	8.5	24	23	24	24	18000	359	△
186357	LV.F-80-24-AS-SST-M16x158-VD	80	M16	54	201	204	158	43	8.5	24	23	24	24	18000	387	△
186361	LV.F-80-24-AS-SST-M20x98-VD	80	M20	54	141	144	98	43	8.5	24	23	24	24	18000	380	△
186363	LV.F-80-24-AS-SST-M20x138-VD	80	M20	54	181	184	138	43	8.5	24	23	24	24	18000	460	△
186365	LV.F-80-24-AS-SST-M20x158-VD	80	M20	54	201	204	158	43	8.5	24	23	24	24	18000	500	△
186367	LV.F-80-24-AS-SST-M20x198-VD	80	M20	54	241	244	198	43	8.5	24	23	24	24	18000	585	△
186371	LV.F-80-24-AS-SST-M24x98-VD	80	M24	54	141	144	98	43	8.5	24	23	24	24	18000	480	△
186373	LV.F-80-24-AS-SST-M24x158-VD	80	M24	54	201	204	158	43	8.5	24	23	24	24	18000	655	△
186375	LV.F-80-24-AS-SST-M24x198-VD	80	M24	54	241	244	198	43	8.5	24	23	24	24	18000	776	△

品號	描述	D	d	d1	L	L1	l	l1	d2	h	h1	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
186401	LV.F-100-14-AS-SST-M8x43-VD	100	M8	70	76	79	43	33	12.5	24	23	14	14	18000	148	△
186403	LV.F-100-14-AS-SST-M8x68-VD	100	M8	70	101	104	68	33	12.5	24	23	14	14	18000	160	△
186411	LV.F-100-14-AS-SST-M10x43-VD	100	M10	70	76	79	43	33	12.5	24	23	14	14	18000	157	△
186413	LV.F-100-14-AS-SST-M10x68-VD	100	M10	70	101	104	68	33	12.5	24	23	14	14	18000	169	△
186415	LV.F-100-14-AS-SST-M10x98-VD	100	M10	70	131	134	98	33	12.5	24	23	14	14	18000	183	△
186421	LV.F-100-14-AS-SST-M12x43-VD	100	M12	70	76	79	43	33	12.5	24	23	14	14	18000	167	△
186423	LV.F-100-14-AS-SST-M12x68-VD	100	M12	70	101	104	68	33	12.5	24	23	14	14	18000	184	△
186425	LV.F-100-14-AS-SST-M12x98-VD	100	M12	70	131	134	98	33	12.5	24	23	14	14	18000	205	△
186431	LV.F-100-14-AS-SST-M14x68-VD	100	M14	70	101	104	68	33	12.5	24	23	14	14	18000	206	△
186433	LV.F-100-14-AS-SST-M14x98-VD	100	M14	70	131	134	98	33	12.5	24	23	14	14	18000	227	△
186435	LV.F-100-14-AS-SST-M14x148-VD	100	M14	70	181	184	148	33	12.5	24	23	14	14	18000	310	△
186441	LV.F-100-14-AS-SST-M16x68-VD	100	M16	70	101	104	68	33	12.5	24	23	16	14	18000	228	△
186443	LV.F-100-14-AS-SST-M16x108-VD	100	M16	70	141	144	108	33	12.5	24	23	16	14	18000	280	△
186445	LV.F-100-14-AS-SST-M16x148-VD	100	M16	70	181	184	148	33	12.5	24	23	16	14	18000	332	△
186447	LV.F-100-14-AS-SST-M16x168-VD	100	M16	70	201	204	168	33	12.5	24	23	16	14	18000	358	△
186451	LV.F-100-24-AS-SST-M16x58-VD	100	M16	70	101	104	58	43	12.5	24	23	24	24	25000	314	△
186453	LV.F-100-24-AS-SST-M16x98-VD	100	M16	70	141	144	98	43	12.5	24	23	24	24	25000	366	△
186455	LV.F-100-24-AS-SST-M16x138-VD	100	M16	70	181	184	138	43	12.5	24	23	24	24	25000	417	△
186457	LV.F-100-24-AS-SST-M16x158-VD	100	M16	70	201	204	158	43	12.5	24	23	24	24	25000	445	△
186461	LV.F-100-24-AS-SST-M20x98-VD	100	M20	70	141	144	98	43	12.5	24	23	24	24	25000	438	△
186463	LV.F-100-24-AS-SST-M20x138-VD	100	M20	70	181	184	138	43	12.5	24	23	24	24	25000	518	△
186465	LV.F-100-24-AS-SST-M20x158-VD	100	M20	70	201	204	158	43	12.5	24	23	24	24	25000	558	△
186467	LV.F-100-24-AS-SST-M20x198-VD	100	M20	70	241	244	198	43	12.5	24	23	24	24	25000	643	△
186471	LV.F-100-24-AS-SST-M24x98-VD	100	M24	70	141	144	98	43	12.5	24	23	24	24	25000	538	△
186473	LV.F-100-24-AS-SST-M24x158-VD	100	M24	70	201	204	158	43	12.5	24	23	24	24	25000	713	△
186475	LV.F-100-24-AS-SST-M24x198-VD	100	M24	70	241	244	198	43	12.5	24	23	24	24	25000	834	△
186501	LV.F-125-24-AS-SST-M16x58-VD	125	M16	95	125	128	58	67	12.5	46	23	24	24	28000	524	△
186503	LV.F-125-24-AS-SST-M16x98-VD	125	M16	95	165	168	98	67	12.5	46	23	24	24	28000	576	△
186505	LV.F-125-24-AS-SST-M16x138-VD	125	M16	95	205	208	138	67	12.5	46	23	24	24	28000	627	△
186507	LV.F-125-24-AS-SST-M16x158-VD	125	M16	95	225	228	158	67	12.5	46	23	24	24	28000	655	△
186511	LV.F-125-24-AS-SST-M20x98-VD	125	M20	95	165	168	98	67	12.5	46	23	24	24	28000	648	△
186513	LV.F-125-24-AS-SST-M20x138-VD	125	M20	95	205	208	138	67	12.5	46	23	24	24	28000	728	△
186515	LV.F-125-24-AS-SST-M20x158-VD	125	M20	95	225	228	158	67	12.5	46	23	24	24	28000	768	△
186517	LV.F-125-24-AS-SST-M20x198-VD	125	M20	95	265	268	198	67	12.5	46	23	24	24	28000	853	△
186521	LV.F-125-24-AS-SST-M24x98-VD	125	M24	95	165	168	98	67	12.5	46	23	24	24	28000	748	△
186523	LV.F-125-24-AS-SST-M24x158-VD	125	M24	95	225	228	158	67	12.5	46	23	24	24	28000	923	△
186525	LV.F-125-24-AS-SST-M24x198-VD	125	M24	95	265	268	198	67	12.5	46	23	24	24	28000	1044	△

PS. 備註

- 使用溫度：-30°C~100°C
- 透過兩個180°的盲孔用於地面安裝，使用工具敲穿塑膠隔膜(參見圖1)

訂貨： 交期： 天

186301

SP. 特長

- 由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21和EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易
- 有防滑墊的底座具有優良的固定性能

WA. 注意

- 如果超過上表最大靜態荷重，可能會導致底座破裂
- 為防止運送途中碰傷，腳座(底座與螺栓)採用個別包裝，請客戶自行組立
- 螺帽需個別購買

圖1

