



底座		螺栓		防滑墊	
材質	顏色	材質	材質	硬度	
PA+玻纖	藍	SUS304	NBR	蕭氏A70	

品號	描述	D	d	L	L1	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
184101	LV.A-60-14-AS-SST-M8x43-VD	60	M8	76	79	43	33	24	14	14	14000	82	△
184103	LV.A-60-14-AS-SST-M8x68-VD	60	M8	101	104	68	33	24	14	14	14000	94	△
184111	LV.A-60-14-AS-SST-M10x43-VD	60	M10	76	79	43	33	24	14	14	14000	91	△
184113	LV.A-60-14-AS-SST-M10x68-VD	60	M10	101	104	68	33	24	14	14	14000	104	△
184115	LV.A-60-14-AS-SST-M10x98-VD	60	M10	131	134	98	33	24	14	14	14000	118	△
184121	LV.A-60-14-AS-SST-M12x43-VD	60	M12	76	79	43	33	24	14	14	14000	101	△
184123	LV.A-60-14-AS-SST-M12x68-VD	60	M12	101	104	68	33	24	14	14	14000	119	△
184125	LV.A-60-14-AS-SST-M12x98-VD	60	M12	131	134	98	33	24	14	14	14000	141	△
184131	LV.A-60-14-AS-SST-M14x68-VD	60	M14	101	104	68	33	24	14	14	14000	142	△
184133	LV.A-60-14-AS-SST-M14x98-VD	60	M14	131	134	98	33	24	14	14	14000	163	△
184135	LV.A-60-14-AS-SST-M14x148-VD	60	M14	181	184	148	33	24	14	14	14000	246	△
184141	LV.A-60-14-AS-SST-M16x68-VD	60	M16	101	104	68	33	24	16	14	14000	164	△
184143	LV.A-60-14-AS-SST-M16x108-VD	60	M16	141	144	108	33	24	16	14	14000	218	△
184145	LV.A-60-14-AS-SST-M16x148-VD	60	M16	181	184	148	33	24	16	14	14000	271	△
184147	LV.A-60-14-AS-SST-M16x168-VD	60	M16	201	204	168	33	24	16	14	14000	298	△
184151	LV.A-60-24-AS-SST-M16x58-VD	60	M16	101	104	58	43	24	24	24	18000	227	△
184153	LV.A-60-24-AS-SST-M16x98-VD	60	M16	141	144	98	43	24	24	24	18000	279	△
184155	LV.A-60-24-AS-SST-M16x138-VD	60	M16	181	184	138	43	24	24	24	18000	330	△
184157	LV.A-60-24-AS-SST-M16x158-VD	60	M16	201	204	158	43	24	24	24	18000	358	△
184161	LV.A-60-24-AS-SST-M20x98-VD	60	M20	141	144	98	43	24	24	24	18000	351	△
184163	LV.A-60-24-AS-SST-M20x138-VD	60	M20	181	184	138	43	24	24	24	18000	431	△
184165	LV.A-60-24-AS-SST-M20x158-VD	60	M20	201	204	158	43	24	24	24	18000	471	△
184167	LV.A-60-24-AS-SST-M20x198-VD	60	M20	241	244	198	43	24	24	24	18000	556	△
184171	LV.A-60-24-AS-SST-M24x98-VD	60	M24	141	144	98	43	24	24	24	18000	451	△
184173	LV.A-60-24-AS-SST-M24x158-VD	60	M24	201	204	158	43	24	24	24	18000	626	△
184175	LV.A-60-24-AS-SST-M24x198-VD	60	M24	241	244	198	43	24	24	24	18000	747	△
184201	LV.A-70-14-AS-SST-M8x43-VD	70	M8	71	74	43	28	19	14	14	14000	81	△
184203	LV.A-70-14-AS-SST-M8x68-VD	70	M8	96	99	68	28	19	14	14	14000	93	△
184211	LV.A-70-14-AS-SST-M10x43-VD	70	M10	71	74	43	28	19	14	14	14000	90	△
184213	LV.A-70-14-AS-SST-M10x68-VD	70	M10	96	99	68	28	19	14	14	14000	103	△
184215	LV.A-70-14-AS-SST-M10x98-VD	70	M10	126	129	98	28	19	14	14	14000	117	△
184221	LV.A-70-14-AS-SST-M12x43-VD	70	M12	71	74	43	28	19	14	14	14000	100	△
184223	LV.A-70-14-AS-SST-M12x68-VD	70	M12	96	99	68	28	19	14	14	14000	118	△
184225	LV.A-70-14-AS-SST-M12x98-VD	70	M12	126	129	98	28	19	14	14	14000	140	△
184231	LV.A-70-14-AS-SST-M14x68-VD	70	M14	96	99	68	28	19	14	14	14000	141	△
184233	LV.A-70-14-AS-SST-M14x98-VD	70	M14	126	129	98	28	19	14	14	14000	162	△
184235	LV.A-70-14-AS-SST-M14x148-VD	70	M14	176	179	148	28	19	14	14	14000	245	△
184241	LV.A-70-14-AS-SST-M16x68-VD	70	M16	96	99	68	28	19	16	14	14000	163	△
184243	LV.A-70-14-AS-SST-M16x108-VD	70	M16	136	139	108	28	19	16	14	14000	217	△
184245	LV.A-70-14-AS-SST-M16x148-VD	70	M16	176	179	148	28	19	16	14	14000	270	△
184247	LV.A-70-14-AS-SST-M16x168-VD	70	M16	196	199	168	28	19	16	14	14000	297	△
184301	LV.A-80-14-AS-SST-M8x43-VD	80	M8	76	79	43	33	24	14	14	16000	110	△
184303	LV.A-80-14-AS-SST-M8x68-VD	80	M8	101	104	68	33	24	14	14	16000	122	△
184311	LV.A-80-14-AS-SST-M10x43-VD	80	M10	76	79	43	33	24	14	14	16000	119	△
184313	LV.A-80-14-AS-SST-M10x68-VD	80	M10	101	104	68	33	24	14	14	16000	132	△
184315	LV.A-80-14-AS-SST-M10x98-VD	80	M10	131	134	98	33	24	14	14	16000	146	△
184321	LV.A-80-14-AS-SST-M12x43-VD	80	M12	76	79	43	33	24	14	14	16000	129	△

品號	描述	D	d	L	L1	l	l1	h	s	螺栓球頭 (ø)	最大靜態荷重 (N)	質量 g	庫存
184323	LV.A-80-14-AS-SST-M12x68-VD	80	M12	101	104	68	33	24	14	14	16000	147	△
184325	LV.A-80-14-AS-SST-M12x98-VD	80	M12	131	134	98	33	24	14	14	16000	169	△
184331	LV.A-80-14-AS-SST-M14x68-VD	80	M14	101	104	68	33	24	14	14	16000	170	△
184333	LV.A-80-14-AS-SST-M14x98-VD	80	M14	131	134	98	33	24	14	14	16000	191	△
184335	LV.A-80-14-AS-SST-M14x148-VD	80	M14	181	184	148	33	24	14	14	16000	274	△
184341	LV.A-80-14-AS-SST-M16x68-VD	80	M16	101	104	68	33	24	16	14	16000	192	△
184343	LV.A-80-14-AS-SST-M16x108-VD	80	M16	141	144	108	33	24	16	14	16000	246	△
184345	LV.A-80-14-AS-SST-M16x148-VD	80	M16	181	184	148	33	24	16	14	16000	299	△
184347	LV.A-80-14-AS-SST-M16x168-VD	80	M16	201	204	168	33	24	16	14	16000	326	△
184351	LV.A-80-24-AS-SST-M16x58-VD	80	M16	101	104	58	43	24	24	24	18000	254	△
184353	LV.A-80-24-AS-SST-M16x98-VD	80	M16	141	144	98	43	24	24	24	18000	306	△
184355	LV.A-80-24-AS-SST-M16x138-VD	80	M16	181	184	138	43	24	24	24	18000	357	△
184357	LV.A-80-24-AS-SST-M16x158-VD	80	M16	201	204	158	43	24	24	24	18000	385	△
184361	LV.A-80-24-AS-SST-M20x98-VD	80	M20	141	144	98	43	24	24	24	18000	378	△
184363	LV.A-80-24-AS-SST-M20x138-VD	80	M20	181	184	138	43	24	24	24	18000	458	△
184365	LV.A-80-24-AS-SST-M20x158-VD	80	M20	201	204	158	43	24	24	24	18000	498	△
184367	LV.A-80-24-AS-SST-M20x198-VD	80	M20	241	244	198	43	24	24	24	18000	583	△
184371	LV.A-80-24-AS-SST-M24x98-VD	80	M24	141	144	98	43	24	24	24	18000	478	△
184373	LV.A-80-24-AS-SST-M24x158-VD	80	M24	201	204	158	43	24	24	24	18000	653	△
184375	LV.A-80-24-AS-SST-M24x198-VD	80	M24	241	244	198	43	24	24	24	18000	774	△
184401	LV.A-100-14-AS-SST-M8x43-VD	100	M8	76	79	43	33	24	14	14	18000	146	△
184403	LV.A-100-14-AS-SST-M8x68-VD	100	M8	101	104	68	33	24	14	14	18000	158	△
184411	LV.A-100-14-AS-SST-M10x43-VD	100	M10	76	79	43	33	24	14	14	18000	155	△
184413	LV.A-100-14-AS-SST-M10x68-VD	100	M10	101	104	68	33	24	14	14	18000	167	△
184415	LV.A-100-14-AS-SST-M10x98-VD	100	M10	131	134	98	33	24	14	14	18000	181	△
184421	LV.A-100-14-AS-SST-M12x43-VD	100	M12	76	79	43	33	24	14	14	18000	165	△
184423	LV.A-100-14-AS-SST-M12x68-VD	100	M12	101	104	68	33	24	14	14	18000	182	△
184425	LV.A-100-14-AS-SST-M12x98-VD	100	M12	131	134	98	33	24	14	14	18000	203	△
184431	LV.A-100-14-AS-SST-M14x68-VD	100	M14	101	104	68	33	24	14	14	18000	204	△
184433	LV.A-100-14-AS-SST-M14x98-VD	100	M14	131	134	98	33	24	14	14	18000	225	△
184435	LV.A-100-14-AS-SST-M14x148-VD	100	M14	181	184	148	33	24	14	14	18000	308	△
184441	LV.A-100-14-AS-SST-M16x68-VD	100	M16	101	104	68	33	24	16	14	18000	226	△
184443	LV.A-100-14-AS-SST-M16x108-VD	100	M16	141	144	108	33	24	16	14	18000	278	△
184445	LV.A-100-14-AS-SST-M16x148-VD	100	M16	181	184	148	33	24	16	14	18000	330	△
184447	LV.A-100-14-AS-SST-M16x168-VD	100	M16	201	204	168	33	24	16	14	18000	356	△
184451	LV.A-100-24-AS-SST-M16x58-VD	100	M16	101	104	58	43	24	24	24	25000	308	△
184453	LV.A-100-24-AS-SST-M16x98-VD	100	M16	141	144	98	43	24	24	24	25000	411	△
184455	LV.A-100-24-AS-SST-M16x138-VD	100	M16	181	184	138	43	24	24	24	25000	411	△
184457	LV.A-100-24-AS-SST-M16x158-VD	100	M16	201	204	158	43	24	24	24	25000	439	△
184461	LV.A-100-24-AS-SST-M20x98-VD	100	M20	141	144	98	43	24	24	24	25000	432	△
184463	LV.A-100-24-AS-SST-M20x138-VD	100	M20	181	184	138	43	24	24	24	25000	512	△
184465	LV.A-100-24-AS-SST-M20x158-VD	100	M20	201	204	158	43	24	24	24	25000	552	△
184467	LV.A-100-24-AS-SST-M20x198-VD	100	M20	241	244	198	43	24	24	24	25000	637	△
184471	LV.A-100-24-AS-SST-M24x98-VD	100	M24	141	144	98	43	24	24	24	25000	532	△
184473	LV.A-100-24-AS-SST-M24x158-VD	100	M24	201	204	158	43	24	24	24	25000	707	△
184475	LV.A-100-24-AS-SST-M24x198-VD	100	M24	241	244	198	43	24	24	24	25000	828	△
184501	LV.A-125-24-AS-SST-M16x58-VD	125	M16	125	128	58	67	46	24	24	28000	515	△
184503	LV.A-125-24-AS-SST-M16x98-VD	125	M16	165	168	98	67	46	24	24	28000	567	△
184505	LV.A-125-24-AS-SST-M16x138-VD	125	M16	205	208	138	67	46	24	24	28000	618	△
184507	LV.A-125-24-AS-SST-M16x158-VD	125	M16	225	228	158	67	46	24	24	28000	646	△
184511	LV.A-125-24-AS-SST-M20x98-VD	125	M20	165	168	98	67	46	24	24	28000	639	△
184513	LV.A-125-24-AS-SST-M20x138-VD	125	M20	205	208	138	67	46	24	24	28000	759	△
184515	LV.A-125-24-AS-SST-M20x158-VD	125	M20	225	228	158	67	46	24	24	28000	759	△
184517	LV.A-125-24-AS-SST-M20x198-VD	125	M20	265	268	198	67	46	24	24	28000	844	△
184521	LV.A-125-24-AS-SST-M24x98-VD	125	M24	165	168	98	67	46	24	24	28000	739	△
184523	LV.A-125-24-AS-SST-M24x158-VD	125	M24	225	228	158	67	46	24	24	28000	914	△
184525	LV.A-125-24-AS-SST-M24x198-VD	125	M24	265	268	198	67	46	24	24	28000	1035	△

PS. 備註

・使用溫度：-30°C~100°C

訂貨： 交期：天

184101

SP. 特長

- ・由RAL 5005「藍」PA製成，符合FDA標準(FDA CFR.21和EU 10/2011)，適合用於食品行業，可輕鬆用人眼辨別食品污染，目檢容易
- ・有防滑墊的底座具有優良的固定性能

WA. 注意

- ・如果超過上表最大靜態荷重，可能會導致底座破裂
- ・為防止運送途中碰傷，腳座(底座與螺栓)採用個別包裝，請客戶自行組立
- ・螺帽需個別購買